

**009L6454****Shut-off ball valve, GBCT 42s**

Inlet connection type: Solder, ODF, Outlet connection type: Solder, ODF, Inlet size [in]: 1 5/8 in, Outlet size [in]: 1 5/8 in

PRODUCT DETAILS

Gross weight	3.272 Kilogram
Net weight	2.94 Kilogram
Volume	4.171 Liter
EAN	5702428559416
Type	GBCT 42s
Product group	Shut-off and regulating valves
Product Name Description	Shut-off ball valve
Access port	Yes
Approval	C UL US LISTED CE EAC
Body material	Brass
CE evaluated	Yes
China RoHS compliance	Yes with exemptions
Connection material	Copper
Contains batteries	No
Cv value [gal/min]	96.1 gal/min
Direction	Straightway
Equipment	Cap w. wire seal
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(c)
Flow direction	Bi-flow
Flow direction indicator	Laser engraved 2-way arrow
Ignition source assessment	Yes
Inlet connection type	Solder, ODF
Inlet size [in]	1 5/8 in
Kv value [m³/h]	83.1 m ³ /h
Max. Working Pressure [bar]	140 bar
Max. Working Pressure [psig]	2031 psig
Outlet connection type	Solder, ODF
Outlet size [in]	1 5/8 in
Packing format	Multi pack
Parts included	Schrader valve
Quantity per packing format	4 pc
Refrigerants	R744
Temperature range [°C] [max]	149 °C
Temperature range [°C] [min]	-40 °C
Temperature range [°F] [max]	300 °F

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

PRODUCT DETAILS

Temperature range [°F] [min]	-40 °F
UL approved refrigerants	R744
UL evaluated	Yes

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Accessories

We're sorry, but the requested information is currently unavailable.

This may be because accessories for this product are not available or the data is incomplete.

For the latest and most accurate information, please visit store.danfoss.com.

Thank you for your understanding.

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.