

**020B1012****Check valve, NRV 12s, Max. Working Pressure [bar]: 49**

Inlet connection type: Solder, ODF, Outlet connection type: Solder, ODF,

Direction: Straightway, Packing format: Multi pack

PRODUCT DETAILS

Gross weight	0.098 Kilogram
Net weight	0.087 Kilogram
Volume	0.152 Liter
EAN	5702428291231
Type	NRV 12s
Product group	Check valves
Product Name Description	Check valve
Approval	C UL US LISTED EAC LLC CDC EURO-TYSK
Body material	Brass
China RoHS compliance	Yes with exemptions
Connection material	Copper
Contains batteries	No
Cv value [gal/min]	2.8 gal/min
Design	Piston
Direction	Straightway
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(c)
Flow direction	Single-flow
Flow direction indicator	On product label
Fluid Group	1 2
Identical product	020B1155
Ignition source assessment	Yes
Inlet connection type	Solder, ODF
Inlet size [in]	1/2 in
Kv value [m³/h]	2.42 m ³ /h
Lubricants compatibility	Oilfree applications
Max. Working Pressure [bar]	49 bar
Max. Working Pressure [psig]	710 psig
Min. Pressure drop [bar]	0.05 bar
Min. Pressure drop [psi]	0.7 psi
MinODP [bar]	0.02 bar
MinODP [psi]	0.29 psi
Oil free refrigerants	R1234ze(E) R134a R513A R515B

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Check valve, NRV 12s, Max. Working Pressure [bar]: 49
PRODUCT DETAILS

	R516A
Outlet connection type	Solder, ODF
Outlet size [in]	1/2 in
Packing format	Multi pack
PED category	Art. 4, par. 3
Quantity per packing format	24 pc
Rated cap cond, Hot gas [IMP]	tcond=86 °F tdisc=176 °F tevap=14 °F thotgas=140 °F tsub=9 °F
Rated cap cond, Hot gas [SI]	tcond=30 °C tdisc=80 °C tevap=-10 °C thotgas=60 °C tsub=5K
Rated cap cond, Liq. cap [IMP]	tcond=86 °F tevap=14 °F tsub=9 °F
Rated cap cond, Liq. cap [SI]	tcond=30 °C tevap=-10 °C tsub=5K
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Refrigerants	R1233zd(E) R1234yf R1234ze(E) R1270 R134a R170 R22/R407C R290 R32 R404A/R507A R407A R407F R407H R410A R448A R449A R449B R450A R452A R452B R454A R454B R454C R455A R513A R515B R516A R600 R600a
SCIP dossier no.	7b42224f-9b93-4833-96e4-aafa2349a423

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Check valve, NRV 12s, Max. Working Pressure [bar]: 49
PRODUCT DETAILS

SCIP dossier product name	NRV V2
Temperature range [°C] [max]	155 °C
Temperature range [°C] [min]	-50 °C
Temperature range [°F] [max]	311 °F
Temperature range [°F] [min]	-58 °F
UL approval file name	REFRIGERANT VALVE 53R0
UL approved refrigerants	R1233zd(E) R1234yf R1234ze(E) R1270 R134a R170 R22 R290 R32 R404A R407A R407C R407F R407H R410A R448A R449A R449B R450A R452A R452B R454A R454B R454C R455A R507A R513A R515B R516A R600 R600a
UL evaluated	Yes

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories

We're sorry, but the requested information is currently unavailable.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

This may be because accessories for this product are not available or the data is incomplete.

For the latest and most accurate information, please visit store.danfoss.com.

Thank you for your understanding.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.