



Q2A-A2006-AAA

Inverter Q2A, 200 V, ND: 6 A / 1.1 kW, HD: 5 A / 0.75 kW, IP20, max. output freq. 590 Hz

Specifications

Drive control method	Closed loop V/f, Closed loop vector, Open loop V/f, Open loop vector
Drive supply voltage	230 V three phase
Max. motor output at constant torque	0.75 kW
Max. motor output at variable torque	1.1 kW
Built in EMC filter	✓
Degree of protection (IP)	IP20
Finless type	✗
Compatible motor type	Induction or asynchronous motor, Permanent magnet motor, Synchronous reluctance motor
Regenerative solutions	As inverter option
Communication port(s)	MODBUS Slave, Serial RS-485, USB
Communication option(s)	Bluetooth, CANopen, DeviceNet Slave, EtherCAT Slave, EtherNet/IP, POWERLINK, PROFIBUS DP Slave, PROFINET Slave
Product Height (unpacked)	260 mm
Product Width (unpacked)	312 mm
Product Depth (unpacked)	176 mm
Product Weight (unpacked)	3100 g

AX-FER2102-PE

Ferrite choke, 21mm diameter, for 2.2kW inverters and below



AX-RAO07600042-DE

AC output reactor, 4.2 A, 7.6 mH, for 0.7 kW, 200 VAC, 1/3 phase



AX-RC06750061-DE

DC link reactor, 6.1 A, 6.75 mH, for 0.4 kW and 0.7 kW, 200 VAC



Q2-FIA4010-SE

Q2A footprint RFI filter, 10 A, 3~ 400 VAC, for 4002, 4004, 4005, 4007 models