



Q2A-A2360-AAA

Inverter Q2A, 200 V, ND: 360 A / 110 kW, HD: 346 A / 90 kW, IP20, max. output freq. 590 Hz

Specifications

Drive control method	Closed loop V/f, Closed loop vector, Open loop V/f, Open loop vector
Drive supply voltage	230 V three phase
Max. motor output at constant torque	90 kW
Max. motor output at variable torque	110 kW
Built in EMC filter	✓
Degree of protection (IP)	IP20
Finless type	✗
Compatible motor type	Induction or asynchronous motor, Permanent magnet motor, Synchronous reluctance motor
Regenerative solutions	As inverter option
Communication port(s)	MODBUS Slave, Serial RS-485, USB
Communication option(s)	Bluetooth, CANopen, DeviceNet Slave, EtherCAT Slave, EtherNet/IP, POWERLINK, PROFIBUS DP Slave, PROFINET Slave
Product Height (unpacked)	800 mm
Product Width (unpacked)	480 mm
Product Depth (unpacked)	472 mm
Product Weight (unpacked)	98000 g

Accessories



Q2-FIA4410-SE

Q2A Busbar termination RFI filter, 410 A, 3~ 400 VAC, for 4208, 4250, 4296, 4371, 4389 models / For 4675 model, 2 units are needed

