



E3ZM-D62 2M

Photoelectric sensor, rectangular housing, stainless steel, infrared LED, diffuse, 1 m, NPN, Light-ON/Dark-ON, 2 m cable

Specifications

| | |
|----------------------------------|--------------------|
| Shape | Cuboid |
| Sensing method | Diffuse reflective |
| Sensing distance | 1000 mm |
| Setting method | Manual adjustment |
| Connection method | Cable |
| Cable length | 2 m |
| Output type | NPN |
| Operation mode | Dark-ON, Light-ON |
| Response time | 1 ms |
| Material housing | Stainless steel |
| Thread size | Other |
| Product Width (unpacked) | 10.8 mm |
| Product Height (unpacked) | 32.2 mm |
| Product Depth (unpacked) | 21 mm |
| Type of light | Infrared light |
| Power supply voltage | 10-30 V |
| Features | Wide beam |
| Degree of protection (IP) | IP67/IP69K |



E39-L104

Mounting bracket for E3Z sensor, standard, vertical mounting



E39-L142

Mounting Bracket, protective side wall (for E3Z)



E39-L144

Sensor mounting Bracket, Protective bracket for E3Z pre-wired



E39-L150

Sensor mounting Bracket for E3Z, 100mm high post



E39-L151

Sensor mounting Bracket, for E3Z, 200mm high post



E39-L153

Mounting bracket for E3Z sensor, L shape, for prewired



E39-L43

Mounting bracket for E3Z sensor, side mounting



E39-L44


Mounting bracket for E3Z sensor, rear mounting



E39-L98

Protective metal cover for E3S-A/E3Z vertical sensor

CAD Library



E3Z Brochure

EN PDF 1.34 MB



E3ZM Photoelectric Sensor, Compact, Stainless steel Datasheet

EN PDF 458 KB



E3ZM-___ Instruction Sheet

EN PDF 1.75 MB



EAC Mark removal Discontinuation Notice

EN PDF 221 KB