

FL SWITCH 1000T-8POE-GT-2SFP - Industrial Ethernet Switch



1026929

<https://www.phoenixcontact.com/gb/products/1026929>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Unmanaged PoE Switch 1000 series, 2 SFP ports 1000 Mbps, 8 RJ45 ports 10/100/1000 Mbps, degree of protection: IP30, Ambient temperature (operation): -40 °C ... 75 °C, Supply voltage range: 18 V DC ... 57 V DC

Your advantages

- Auto negotiation
- Autocrossing
- Wide temperature range -40 °C ... +75 °C
- Wide-range power supply of 18 ... 57 V DC
- POE status LED per port
- Redundant power supply
- Automatic detection of IEEE 802.3at or 802.3af powered devices

Commercial data

Item number	1026929
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DNN115
Product key	DNN115
GTIN	4055626519975
Weight per piece (including packing)	1,469 g
Weight per piece (excluding packing)	1,151 g
Customs tariff number	85176200
Country of origin	TW

FL SWITCH 1000T-8POE-GT-2SFP - Industrial Ethernet Switch



1026929

<https://www.phoenixcontact.com/gb/products/1026929>

Technical data

Dimensions

Width	63.5 mm
Height	145 mm
Depth	136 mm

Notes

Notes on operation	Mode A PoE
--------------------	------------

Mounting

Mounting type	DIN rail mounting
---------------	-------------------

Interfaces

Fiber optic interface

Connection method	SFP
Transmission speed	1000 Mbps (full duplex)
Transmission physics	Depending on the SFP module
Transmission length	up to 80 km (Depending on the fiber/SFP module used)
No. of channels	2 (SFP ports)

Ethernet (PoE)

Connection method	RJ45 jack
Transmission speed	10/100/1000 Mbps
Transmission physics	Ethernet RJ45
Transmission length	100 m (Between transmitter / receiver)
Signal LEDs	LNK/ACT, POE
No. of channels	8 (RJ45 ports)

Product properties

Product type	Switch
Product family	Unmanaged PoE Switch 1000
Type	Stand-alone
MTTF	39.1 Years (MIL-HDBK-217F standard, temperature 25°C, operating cycle 100%)
Basic functions	Store-and-forward switch, 10/100/1000 Mbps, auto negotiation, redundant power supply, PoE according to IEEE 802.3at/802.3af, jumbo frames up to 10240 bytes, alarm contact

Switch functions

Basic functions	Store-and-forward switch, 10/100/1000 Mbps, auto negotiation, redundant power supply, PoE according to IEEE 802.3at/802.3af, jumbo frames up to 10240 bytes, alarm contact
Signal contact control voltage	48 V DC

FL SWITCH 1000T-8POE-GT-2SFP - Industrial Ethernet Switch



1026929

<https://www.phoenixcontact.com/gb/products/1026929>

Signal contact control current	0.5 A
Status and diagnostic indicators	LEDs: U _{S1} , U _{S2} (redundant voltage supply), Alarm (alarm contact), Link/Activity and PoE per Ethernet port
Additional functions	Autonegotiation

Security functions

Basic functions	Store-and-forward switch, 10/100/1000 Mbps, auto negotiation, redundant power supply, PoE according to IEEE 802.3at/802.3af, jumbo frames up to 10240 bytes, alarm contact
-----------------	--

Electrical properties

Local diagnostics	US1, US2 Supply voltage Green LED
	PoE PoE detection Orange LED
	LNK/ACT Link status/data transmission Green LED
	Alarm Power failure at US1 or US2/Link failure

Supply

Supply voltage (DC)	24 V DC
	48 V DC
Supply voltage range	18 V DC ... 57 V DC
Power supply connection	Via COMBICON, max. conductor cross-section 2.5 mm ²
Inrush current	30.8 A (24 V DC for 1050 µs)
Residual ripple	3.6 V _{PP} (within the permitted voltage range)
Max. current consumption	6.2 A (Maximum, nominal load)
Typical current consumption	470 mA (at U _S = 24 V DC)

Function

Signal contact control voltage	48 V DC
Signal contact control current	0.5 A

Connection data

Connection technology

Connection name	Power supply
-----------------	--------------

Power supply

Connection method	COMBICON plug-in screw terminal block
Conductor cross-section, rigid	0.2 mm ² ... 2.5 mm ²
Conductor cross-section, flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross-section AWG	24 ... 12
Stripping length	7 mm

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP30
Ambient temperature (operation)	-40 °C ... 75 °C

FL SWITCH 1000T-8POE-GT-2SFP - Industrial Ethernet Switch



1026929

<https://www.phoenixcontact.com/gb/products/1026929>

Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	5 % ... 95 % (non-condensing)
Air pressure (operation)	57 kPa ... 108 kPa (up to 4850 m above mean sea level)
Air pressure (storage/transport)	57 kPa ... 108 kPa (up to 4850 m above mean sea level)

Approvals

Conformity/Approvals

Conformance	CE-compliant
-------------	--------------

EMC data

Electromagnetic compatibility	Conformance with EMC Directive 2004/108/EC
Conformance with EMC directives	IEC 61000-6-2 IEC 61000-4-2 (ESD) Criterion B
	IEC 61000-4-3 (immunity to radiated interference) Criterion A
	IEC 61000-4-4 (burst) Criterion A
	IEC 61000-4-5 (surge) Criterion B
	IEC 61000-4-6 (immunity to conducted interference) Criterion A
	IEC 61000-4-8 (immunity to magnetic fields) Criterion A
Noise immunity	EN 55022 (emitted interference) Criterion A
	EN 61000-6-2:2019

Noise emission

Standards/regulations	EN_61000-6-4:2019
-----------------------	-------------------

System properties

Functionality

Basic functions	Store-and-forward switch, 10/100/1000 Mbps, auto negotiation, redundant power supply, PoE according to IEEE 802.3at/802.3af, jumbo frames up to 10240 bytes, alarm contact
-----------------	--

Signaling

Status display	LEDs: U _{S1} , U _{S2} (redundant voltage supply), Alarm (alarm contact), Link/Activity and PoE per Ethernet port
----------------	--

FL SWITCH 1000T-8POE-GT-2SFP - Industrial Ethernet Switch



1026929

<https://www.phoenixcontact.com/gb/products/1026929>

Classifications

UNSPSC

UNSPSC 21.0	43222612
-------------	----------

FL SWITCH 1000T-8POE-GT-2SFP - Industrial Ethernet Switch



1026929

<https://www.phoenixcontact.com/gb/products/1026929>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	15(a), 6(a)-I, 6(c), 7(a), 7(c)-I, 7(c)-IV

China RoHS

Environment friendly use period (EFUP)	EFUP-10
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
-------------------------------------	----------------------

Phoenix Contact 2025 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk