

# Product datasheet

Specifications



## Universal Mounting Accessory, XV4/ XV6/XVB7 Modular Tower Light, Plastic Fixing Plate With Pole, Grey

XVZ02

EAN Code: 3606487130437

### Main

Product or component type	Accessory
Accessory / separate part type	Plastic fixing plate with pole
Product compatibility	XVB7..... XV6..... XV4.....
Material	Plastic
Provided accessory	Gasket
Net weight	0.081 kg

### Complementary

Height	110 mm
cable entry	Bottom entry
Colour	Dark grey

### Environment

IP degree of protection	IP66
Environmental Type ratings	Type 4/4X/12/13 indoor use only

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.500 cm
Package 1 Width	7.500 cm
Package 1 Length	7.500 cm
Package 1 Weight	65.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	30
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	2.437 kg
Unit Type of Package 3	P06
Number of Units in Package 3	240

---

Package 3 Height	75.000 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	29.496 kg

---

## Logistical informations

---

Country of origin DE

## Contractual warranty

---

Warranty (in months) 18

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint 1

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

REACH Regulation [REACH Declaration](#)

## Use Again

### Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

Offer Marketing Illustration

Product benefits / Features

---

## Technical Benefits

### Harmony XVB7

Conformity with IEC, CUL and CCC standards, as well as CE marking

Up to IP66 and type 4X protection ratings

High shock and vibration resistance up to 6g



Energy efficient LED with operating life up to 50,000 hours

Save up to 75% wiring time with M12 connection and push-in terminal

High brightness level with illuminance up to 3000cd/m<sup>2</sup>

Offer Marketing Illustration

Product benefits / Features

---

### Features

Harmony XVB7



Sustainability: high brightness with low power consumption realized via energy efficient LED



Elevated design with a modern twist to enhance machine aesthetic



Modular design for adaptability, ease of maintenance and low inventory



Wide base variety with the option to be connected via USB & IO-link base



Adjustable and customizable sounder with maximum sound pressure of up to 102dB

Image of product / Alternate images

Alternative

---





