



 PRODUCT-DETAILS

TA25DU-25-20

TA25DU-25-20 Thermal Overload Relay 18 ... 25 A



General Information

Extended Product Type	TA25DU-25-20
Product ID	1SAZ211401R1051
EAN	4013614376603
Catalog Description	TA25DU-25-20 Thermal Overload Relay 18 ... 25 A

Long Description	<p>The TA25DU-25-20 thermal overload relay is an economic electromechanical protection device for the main circuit. It offers reliable and fast protection for motors in the event of overload or phase failure. The device has trip class 20. Further features are the temperature compensation, trip contact (NC), signal contact (NO), automatic- or manual reset selectable, trip-free mechanism, STOP- and Test function and a trip indication. The overload relays are connected directly to the block contactors. Single mounting kits are available as accessory.</p>
------------------	---

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Instructions and Manuals	2CDC106031M6802
Time-Current Characteristic Curve	1SAZ200503F0011
Dimension Diagram	1SAZ200402F0001

Dimensions

Product Net Width	44 mm
Product Net Height	80 mm
Product Net Depth / Length	94 mm
Product Net Weight	0.2 kg

Technical

Setting Range	18 ... 25 A
Rated Operational Voltage	Auxiliary Circuit 440 V DC Auxiliary Circuit 500 V AC Main Circuit 690 V AC Main Circuit 440 V DC
Rated Operational Current (I_e)	25 A
Rated Frequency (f)	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC Main Circuit 60 Hz Main Circuit 50 Hz Main Circuit DC
Rated Impulse Withstand Voltage (U_{imp})	Auxiliary Circuit 6 kV Main Circuit 6 kV
Rated Insulation Voltage (U_i)	690 V
Number of Poles	3P
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Number of Protected Poles	3
Conventional Free-air Thermal Current (I_{th})	Auxiliary Circuit NC 10 A Auxiliary Circuit NO 6 A
Rated Operational Current AC-15 (I_e)	(120 V) NC 3 A (120 V) NO 1.5 A (240 V) NC 3 A (240 V) NO 1.2 A (400 V) NC 0.75 A (400 V) NO 0.37 A (440 V) NC 0.75 A (440 V) NO 0.37 A (500 V) NC 0.3 A (500 V) NO 0.25 A
Rated Operational Current DC-13 (I_e)	(125 V) NC 0.25 A (125 V) NO 0.25 A (24 V) NC 1.25 A (24 V) NO 1.25 A (250 V) NC 0.12 A (250 V) NO 0.04 A (60 V) NC 0.25 A (60 V) NO 0.25 A
Degree of Protection	Housing IP20

		Main Circuit Terminals IP10
Pollution Degree		3
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible 1/2x 0.75 ... 2.5 mm ² Rigid 1/2x 0.75 ... 4 mm ²	
Connecting Capacity Main Circuit	Flexible with Ferrule 1/2x 1.5 ... 4 mm ² Flexible 1/2x 1.5 ... 4 mm ² Rigid 1/2x 1.5 ... 6 mm ²	
Tightening Torque	Auxiliary Circuit 1 ... 1.3 N·m Main Circuit 1.5 ... 1.9 N·m	
Wire Stripping Length	Auxiliary Circuit 9 mm Main Circuit 12 mm	
Recommended Screw Driver	Auxiliary Circuit Pozidriv 1 Main Circuit Pozidriv 2	
Power Loss	at Rated Operating Conditions per Pole 1.5 ... 3.0 W	
Suitable For		A9 A12 A16 A26 A30 A40 AL9 AL12 AL16 AL26 AL30 AL40
Standards		IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V AC
Contact Rating UL/CSA	(NC:) B600 (NO:) C300
Connecting Capacity Main Circuit UL/CSA	Flexible 1/2x 14-10 AWG Stranded 1/2x 14-10 AWG
Connecting Capacity Auxiliary Circuit UL/CSA	Flexible 1/2x 18-14 AWG Stranded 1/2x 18-14 AWG
Tightening Torque UL/CSA	Auxiliary Circuit 12 in·lb Main Circuit 12 in·lb

Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Operation Compensated -25 ... +55 °C Storage -40 ... +70 °C
Ambient Air Temperature Compensation	Yes
Maximum Operating Altitude Permissible	2000 m
Resistance to Shock acc. to IEC 60068-2-27	11 ms Pulse 12g 25g 2 shocks 13 ms
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006525

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Declaration	2CMT2021-006277
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

ABS Certificate	1SAA941000-0102
BV Certificate	1SAA941000-0201
CB Certificate	1SAA941005-2001
CQC Certificate	CQC2015010309808587
Declaration of Conformity - CCC	2020980304001318
Declaration of Conformity - CE	1SAD101100-3509
Declaration of Conformity - UKCA	1SAD201100-3509
DNV Certificate	1SAA941000-0304
DNV GL Certificate	1SAA941000-0304
EAC Certificate	1SAA941002-2702
GL Certificate	1SAA941000-0304
LR Certificate	1SAA941000-0504
RMRS Certificate	1SAA941000-0704
UL Certificate	E48139-19970507

Container Information

Package Level 1 Units	carton 1 piece
Package Level 1 Width	98 mm
Package Level 1 Height	82 mm
Package Level 1 Depth / Length	47 mm
Package Level 1 Gross Weight	0.22 kg
Package Level 1 EAN	4013614376603
Package Level 2 Units	35 piece
Package Level 2 Width	280 mm
Package Level 2 Height	210 mm
Package Level 2 Depth / Length	395 mm
Package Level 2 Gross Weight	8.086 kg

External Classifications and Standards

Object Classification Code	F
ETIM 9	EC000106 - Thermal overload relay
ETIM 10	EC000106 - Thermal overload relay

eClass	V11.0 : 27371501
UNSPSC	39122330
IDEA Granular Category Code (IGCC)	5366 >> Thermal overload relay

Categories

Low Voltage Products and Systems → Control Products → Contactors → Thermal Overload Relays

