



PRODUCT-DETAILS

# ACS355-03E-01A2-4

LV AC machinery drive module, IEC: Pn 0.37 kW, 1.2 A (ACS355-03E-01A2-4)



General Information	
Global Commercial Alias	ACS355-03E-01A2-4
Product ID	3AUA0000058182
ABB Type Designation	ACS355-03E-01A2-4
EAN	6438177223573
Catalog Description	LV AC machinery drive module, IEC: Pn 0.37 kW, 1.2 A (ACS355-03E-01A2-4)
Long Description	<p>The ACS355 drives are designed to meet the requirements of an extensive range of machinery applications in food and beverage, material handling, lifting, textile, printing, rubber and plastics, and woodworking applications.</p> <p>The drive is user-friendly, yet it provides a wide range of built-in technology such as the safe torque off functionality and sequence programming, reducing the need for additional control electronics. The product offers options and diverse functionality to cater to the needs set for <u>speed and torque control of AC induction and permanent magnet motors.</u></p>

Ordering	
Customs Tariff Number	85044085
HS Code	850440 -- ELECTRICAL MACHINERY AND EQUIPMENT AND PARTS THEREOF; SOUND RECORDERS AND REPRODUCERS, TELEVISION IMAGE AND SOUND RECORDERS AND REPRODUCERS, AND PARTS AND ACCESSORIES OF SUCH ARTICLES;Electrical transformers, static converters (for example, rectifiers) and inductors;Static converters
Invoice Description	ACS355-03E-01A2-4 Pn 0,37kW, I2n 1,2A IP20.

Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

## Dimensions

Product Net Weight	1.7 kg
Product Net Depth / Length	161 mm
Product Net Height	239 mm
Product Net Width	70 mm
Package Level 1 Depth / Length	350 mm
Package Level 1 Height	130 mm
Package Level 1 Width	220 mm
Package Level 1 Units	1 carton

## Technical

Number of Phases	3-phase
Degree of Protection	IP20
Enclosure Type NEMA	Open Type
Multiple Battery Information	No battery / cell included
Frequency (f)	50/60 Hz
Frame Size	R1
Input Voltage ( $U_{in}$ )	380 ... 480 V
Mounting Type	Module for cabinet building
Communication Protocol	MODBUS LON DeviceNet PROFIBUS CAN EtherNet/IP PROFINET IO TCP/IP Other Bus Systems
Number of Hardware Interfaces	Industrial Ethernet 0 PROFINET 0 RS-232 1 RS-422 0 RS-485 1 Serial TTY 0 USB 0 Parallel 0 Other 1
Includes	Without control unit Without optical interface With PC connection
Analog Inputs	2
Analog Outputs	1
Number of Digital In/Outputs	5/1
Output Current, Normal Use ( $I_n$ )	1.2 A
Output Power, Normal Use ( $P_n$ )	0.37 kW
Output Power, Light-Overload Use ( $P_{LD}$ )	0.37 kW

Apparent Power Output	19 W
Efficiency Level	0.8 kV-A
Standby Loss	IE2
Complete Drive Module Efficiency (IEC61800-9-2)	7 W

Operating Point Frequency / Current	Absolute Loss	Relative Loss	Efficiency
0 / 25 %	15 W	1.8 %	78.4 %
0 / 50 %	15 W	1.8 %	84.6 %
0 / 100 %	16 W	2.0 %	89.9 %
50 / 25 %	15 W	1.8 %	88.0 %
50 / 50 %	16 W	1.9 %	91.7 %
50 / 100 %	17 W	2.1 %	94.6 %
90 / 50 %	16 W	2.0 %	95.0 %
90 / 100 %	19 W	2.2 %	96.7 %

Temperature Rating Maximum 40 °C

### Certificates and Declarations

Declaration of Conformity - CE	3AXD10000499279
REACH Date	20250905
REACH Declaration	9AKK107992A7060
REACH Information	True - contains substances > 0.1 mass percentage
RoHS Date	20230303
RoHS Declaration	3AXD10000499279
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

### Environmental

SCIP	82577795-E294-456D-9F6C-5E2854AD42F7 Finland
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

### External Classifications and Standards

ETIM 9	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

### Categories

Drives → Low Voltage AC Drives → Machinery Drives → ACS355 - Machinery Drive

