

SIMATIC process control system IPC547J; (rack PC, 19, 4 U), interfaces: 3x Gbit LAN (RJ45), 1x DVI-D, 2x display port; 1x COM, audio; 6x USB 3.1 Gen. 2 (2x type C, 4x type A) on the rear side, 2x USB3.1 Gen.1 (type A) on the front, 2x USB 2.0 internal; 7 slots: 5x PCIe, 2x PCI, internal, temperature and fan monitoring watchdog, card retainer; Core i7-10700E (8C/16T, 2.9 (4.5) GHz, 16 MB cache), MB (Chipset W480E), iAMT, spare part; RAID1, 2x 1920 GB SSD 2.5 SATA; drive support for internal installation, 0.5 G vibration, 5 g shock; 1024 GB SSD M.2 NVMe (M.2 slot occupied) (for operating system); 64 GB DDR4 SDRAM (2x 32 GB), dual channel; without pre-installation; Windows 10 IoT Enterprise 2021 LTSC, MUI (en, de, fr, it, es, zh), 64-bit, with restore USB flash drive, (for Processor Core i7 / Xeon); enclosure blue chromated, without expansions; 100/240 V AC industrial power supply unit, power supply cord Europe;

Approvals / Certificates

General Product Approval



[Manufacturer Declaration](#)



General Product Approval Environment



[BIS CRS](#)

[KC](#)

[Environmental Confirmations](#)



last modified:

11/11/2025