

**067N2026****Thermostatic expansion valve, TGE, R22/R407C**

Temperature range [°C]: -25 - 10, MOP Point [°C]: 15, Orifice capacities [kW]: 27, Orifice capacities [TR]: 7.5, Pressure equalization: Externally equalized

PRODUCT DETAILS

Gross weight	0.456 Kilogram
Net weight	0.365 Kilogram
Volume	1.584 Liter
EAN	5702428138796
Type	TGE
Product group	Expansion valves
Product Name Description	Thermostatic expansion valve
Approval	C UL US LISTED EAC LLC CDC TYSK
Balanced port [Yes/No]	Yes
Body material	Brass
Capillary tube length [in]	59 in
Capillary tube length [mm]	1500 mm
China RoHS compliance	Out of scope
Connection material	Copper
Contains batteries	No
Direction	Straightway
Element temperature max. [°C]	110 °C
Element temperature max. [°F]	230 °F
EPD available	Yes
Equalization connection type	Solder, ODF
Equalization size [in]	1/4 in
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(c)
Flow direction	Bi-flow
Flow direction indicator	Embossed 1-way arrow
Fluid Group	2
Inlet connection type	Solder, ODF
Inlet size [in]	5/8 in
Max. Working Pressure [bar]	49 bar
Max. Working Pressure [psig]	711 psig
MOP Point [psig]	MOP 100
MOP Point [°C]	15 °C
MOP Point [°F]	60 °F
Orifice capacities [kW]	27 kW
Orifice capacities [TR]	7.5 TR
Orifice size	8

Product Detail | Thermostatic expansion valve, TGE, R22/R407C
PRODUCT DETAILS

Outlet connection type	Solder, ODF
Outlet size [in]	7/8 in
Packing format	Industrial pack
Parts included	Bulb strap
PED category	Art. 4, par. 3
Pressure equalization	Externally equalized
Product accessories	TXV accessories
Quantity per packing format	12 pc
Rated cap. cond. Range N [IMP]	tcond=100 °F tevap=40 °F tliq=98 °F
Rated cap. cond. Range N [SI]	tcond=38 °C tevap=4.4 °C tliq=37 °C
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Refrigerants	R22/R407C
SCIP dossier no.	3c484d77-61a0-4822-8540- e10a4d795088
SCIP dossier product name	TGE -Thermostatic expansion valve
Serviceable	No
Static Superheat (SS) [°C]	4 °C
Static Superheat (SS) [°F]	7.2 °F
Superheat setting	Adjustable
Temperature range [°C] [max]	10 °C
Temperature range [°C] [min]	-25 °C
Temperature range [°F] [max]	50 °F
Temperature range [°F] [min]	-15 °F
UL approved refrigerants	R22 R407C
UL evaluated	Yes

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Accessories

067N0557 [↗](#)
Generic accessories, Bulb clamp, Accessory

Product Type: Accessory, Type designation: Bulb strap, 225 mm, Packing format: Industrial pack,
Quantity per packing format: 40

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.