

**060G1463****Pressure transmitter, MBS 3300, 0 bar - 4 bar, 0 psi - 58 psi**

Pressure reference: Gauge (relative), Output signal: Current, Electrical connection: Angular connector, Pressure connection type: G, Pressure connection size: 1/4, Specification key: MBS 3300-1611-A6FB04-4

PRODUCT DETAILS

Gross weight	0.178 Kilogram
Net weight	0.157 Kilogram
Volume	0.408 Liter
EAN	5702423122646
Type	MBS 3300
Product group	Sensors
Product Name Description	Pressure transmitter
+ supply	Pin 1
- common	Pin 2
Accuracy, max. [\pmFS%]	1 %
Accuracy, typical [\pmFS%]	0.5 %
Adj. zero point and span	No
Ambient temperature range [$^{\circ}$C] [max]	100 $^{\circ}$ C
Ambient temperature range [$^{\circ}$C] [min]	-40 $^{\circ}$ C
Ambient temperature range [$^{\circ}$F] [max]	212 $^{\circ}$ F
Ambient temperature range [$^{\circ}$F] [min]	-40 $^{\circ}$ F
Approval	ATEX CE C UL US UL Recognized
Approval comments	ATEX Ex ec IIA T4 Gc
CE evaluated	Yes
China RoHS compliance	Out of scope
Compensated temp. range [$^{\circ}$C] [max]	100 $^{\circ}$ C
Compensated temp. range [$^{\circ}$C] [min]	0 $^{\circ}$ C
Compensated temp. range [$^{\circ}$F] [max]	212 $^{\circ}$ F
Compensated temp. range [$^{\circ}$F] [min]	32 $^{\circ}$ F
Contains batteries	No
EEE category	5 small equipment (any external dimension < 50 cm)
Electrical conn. Male/Female	Male and Female
Electrical connection	Angular connector

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Pressure transmitter, MBS 3300, 0 bar - 4 bar, 0 psi - 58 psi
PRODUCT DETAILS

Electrical connection size	Pg 11
Electrical connection standard	EN 175301-803-A
Enclosure rating IP	IP65
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(c)
Flush diaphragm	No
High Clipping Level	22.4
In scope of WEEE	No
International Article Number	5702423122646
Intrinsically safe	No
Low Clipping level	3.6
Medium temperature range [°C] [max]	125 °C
Medium temperature range [°C] [min]	-40 °C
Medium temperature range [°F] [max]	257 °F
Medium temperature range [°F] [min]	-40 °F
Non-linearity BFSL [±FS%]	0.5 %
Output signal	Current
Output signal [mA] [max]	20 mA
Output signal [mA] [min]	4 mA
Overload pressure max. [bar]	8 bar
Packing format	Multi pack
Pressure connection HEX [mm]	27 mm
Pressure connection size	1/4
Pressure connection standard	DIN 3852-G
Pressure connection type	G
Pressure Male/Female	Male
Pressure range [bar] [max]	4 bar
Pressure range [bar] [min]	0 bar
Pressure range [psi] [max]	58 psi
Pressure range [psi] [min]	0 psi
Pressure reference	Gauge (relative)
Pulse-snubber	No
Quantity per packing format	14 pc
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Response time max. [ms]	4 ms
SCIP dossier no.	16d2efc6-64f3-4a4e-ae98- a3fd7ce0218d
SCIP dossier product name	AKS/MBS
Specification key	MBS 3300-1611-A6FB04-4
Supply voltage [V] DC [max]	32 V
Supply voltage [V] DC [min]	9 V
UL evaluated	Yes

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**060G0005** [🔗](#)**Accessories, sensors, Electrical connector**

Used for product: AKS/MBS, Parts included: Angular connector M20; Gasket, Packing format: Multi pack, Quantity per packing format: 32

**060G0007** [🔗](#)**Accessories, sensors, Electrical connector**

Used for product: AKS/MBS, Parts included: Angular con. PG11 w.knife cont; Gasket, Packing format: Multi pack, Quantity per packing format: 96

**060G0008** [🔗](#)**Accessories, sensors, Electrical connector**

Used for product: AKS/MBS, Parts included: Gasket; Angular con. PG9 w.knife cont., Packing format: Multi pack, Quantity per packing format: 96

**060G1034** [🔗](#)**Accessories, sensors, Cable**

Used for product: AKS/MBS, Parts included: Plug w. 5,0 m cable, Packing format: Multi pack, Quantity per packing format: 8

**061B6001** [🔗](#)**Isolation valve, MBV 2000**

Max. Working Pressure [bar]: 600, Internal connection type: G

**061B6002** [🔗](#)**Isolation valve, MBV 2000**

Max. Working Pressure [bar]: 600, Internal connection type: G

**061B6100** [🔗](#)**Test valve, MBV 3000**

Pressure connection type: G, Pressure connection size: 1/2, Pressure range (Pi) [bar]: 0 - 120

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.