

## Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7064-5WF74-1NB5




Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

Rated speed	3,000 rpm
Number of poles	10
Rated torque (100 K)	16.0 Nm
Rated current	12.51 A
Static torque (60 K)	12.8 Nm
Static torque (100 K)	16.0 Nm
Stall current (60 K)	9.60 A
Stall current (100 K)	11.90 A
Rotor moment of inertia	15.40 kgcm <sup>2</sup>
Efficiency	91.0 %

### Physical constants

Torque constant	1.34 Nm/A
Voltage constant at 20° C	84.5 V/1000*min <sup>-1</sup>
Winding resistance at 20° C	0.50 Ω
Rotary field inductance	5.3 mH
Electrical time constant	11.00 ms
Mechanical time constant	1.10 ms
Thermal time constant	2 min
Shaft torsional stiffness	26,000 Nm/rad
Net weight of the motor	14.8 kg

### Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	63
Cooling	Water cooling
Radial runout tolerance	0.040 mm
Concentricity tolerance	0.100 mm
Axial runout tolerance	0.100 mm
Vibration severity grade	Grade R
Degree of protection	IP67
Design acc. to Code I	IM B5 (compatible with 1FT6)
Temperature monitoring	Pt1000 temperature sensor
Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Shaft end type	Fitted key and keyway
Sensor design	Encoder IC2048S/R: incremental encoder sin/cos 1 Vpp 2048 S/R with C and D track
Electrical connection	Connector turnable
Connector size	1

### Optimum operating point

Optimum speed	3,000 rpm
Optimum power	5.0 kW

### Limiting data

Max. permissible speed (mech.)	9,000 rpm
Max. permissible speed (inverter)	6,800 rpm
Maximum torque	40.0 Nm
Maximum current	39.30 A

### Recommended Motor Module

Rated inverter current	18.00 A
Maximum inverter current	54.00 A
Maximum torque	40.0 Nm

### Holding brake

Holding brake version	Permanent-magnet brake
Holding torque	18.0 Nm
Braking torque	11.0 Nm
Power supply voltage	DC 24 V
Coil current	0.80 A
Permissible brake work	880 J
Opening time	150 ms
Closing time	50 ms