

Product datasheet

Specifications



Linergy DS - screw distribution block 1P - 250A - 14 holes

Local distributor code:

402645115

LGY125014

EAN Code: 3606480542176

Main

Range	Linergy
Product name	Linergy DS
Product or component type	Distribution block

Complementary

Mounting support	DIN rail
Range compatibility	Prisma G Prisma P Prisma PH Spacial TeSys
Product compatibility	Spacial enclosures
Poles description	1P
Distribution block outgoers	14 holes
[Ue] rated operational voltage	230 V AC Ph/N 440 V AC Ph/Ph
[Ui] rated insulation voltage	500 V AC
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	250 A at 40 °C
[Icw] rated short-time withstand current	14.4 kA for 1 s
[Ipk] rated peak withstand current	60 kA
Connections - terminals	Distribution: screw terminal 4 cable(s) 1.5...16 mm ² rigid Distribution: screw terminal 4 cable(s) 1.5...10 mm ² flexible with cable end Distribution: screw terminal 8 cable(s) 2.5...25 mm ² rigid Distribution: screw terminal 8 cable(s) 1.5...16 mm ² flexible with cable end Supply: screw terminal 1 cable(s) 35...120 mm ² rigid Supply: screw terminal 1 cable(s) 23...95 mm ² flexible with cable end Distribution: screw terminal 1 cable(s) 1.5...50 mm ² rigid Distribution: screw terminal 1 cable(s) 1.5...35 mm ² flexible with cable end
Tightening torque	Distribution: 2 N.m flat screwdriver 7.5 mm Distribution: 2 N.m PZ2 screwdriver 7.5 mm Supply: 10 N.m flat screwdriver 15.3 mm Supply: 10 N.m PZ2 screwdriver 15.3 mm Distribution: 4 N.m flat screwdriver 10 mm Distribution: 4 N.m PZ2 screwdriver 10 mm Distribution: 2 N.m flat screwdriver 6 mm Distribution: 2 N.m PZ2 screwdriver 6 mm
9 mm pitches	5
Height	85 mm
Width	45 mm

Depth	50.5 mm
Net weight	0.252 kg
Colour	White (RAL 9003)

Environment

Pollution degree	3
Overvoltage category	III
Dielectric strength	2500 V
Standards	EN/IEC 60947-7-1 EN/IEC 61439-1
Ambient air temperature for operation	-25...55 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.000 cm
Package 1 Width	5.500 cm
Package 1 Length	9.000 cm
Package 1 Weight	253.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	40
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	10.670 kg
Unit Type of Package 3	P12
Number of Units in Package 3	320
Package 3 Height	45.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	95.500 kg

Logistical informations

Country of origin	TN
-------------------	----

Contractual warranty

Warranty (in months)	18
----------------------	----


Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.



[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	B7c6f1d6-d622-4f6c-907b-f4c3173076cb
REACH Regulation	REACH Declaration
Halogen-free status	Halogen free product
PVC free	Yes

Use Again

 Repack and remanufacture	
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins