

# Product datasheet

Specifications



## Linergy DS - screw distribution block 4P - 100A - 28 holes

LGY410028

EAN Code: 3606480542084

### Main

Range	Linergy
Product name	Linergy DS
Product or component type	Distribution block

### Complementary

Mounting support	DIN rail
Range compatibility	Prisma G Prisma P Prisma PH Prisma Pack Spacial Kaedra Pragma TeSys ComPact
Product compatibility	Spacial enclosures
Poles description	4P
Distribution block outgoers	4 x 7 holes
[Ue] rated operational voltage	230 V AC Ph/N 440 V AC Ph/Ph
[Ui] rated insulation voltage	500 V AC
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	100 A at 40 °C
[Icw] rated short-time withstand current	3 kA for 1 s
[Ipk] rated peak withstand current	24 kA
Connections - terminals	Supply: screw terminal 2 cable(s) 2.5...25 mm <sup>2</sup> rigid Supply: screw terminal 2 cable(s) 1.5...16 mm <sup>2</sup> flexible with cable end Distribution: screw terminal 5 cable(s) 1.5...16 mm <sup>2</sup> rigid Distribution: screw terminal 5 cable(s) 1.5...10 mm <sup>2</sup> flexible with cable end
Tightening torque	Supply: 2 N.m flat screwdriver 7.5 mm Supply: 2 N.m PZ2 screwdriver 7.5 mm Distribution: 2 N.m flat screwdriver 5.5 mm Distribution: 2 N.m PZ2 screwdriver 5.5 mm
9 mm pitches	8
Height	100 mm
Width	71 mm
Depth	50.5 mm
Net weight	0.21 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

---

Colour	White (RAL 9003)
--------	------------------

---

## Environment

---

Pollution degree	3
Overvoltage category	III
Dielectric strength	2500 V
Standards	EN/IEC 61439-1 EN/IEC 60947-7-1
Ambient air temperature for operation	-25...55 °C

---

## Packing Units

---

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.800 cm
Package 1 Width	10.500 cm
Package 1 Length	13.400 cm
Package 1 Weight	245.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	34
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	8.880 kg
Unit Type of Package 3	P12
Number of Units in Package 3	272
Package 3 Height	45.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	84.400 kg

---

## Logistical informations

---

Country of origin	TN
-------------------	----

---

## Contractual warranty

---

Warranty (in months)	18
----------------------	----

---


## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.



[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

 <b>Materials and Substances</b>	
Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
<a href="#">EU RoHS Directive</a>	Compliant with Exemptions
SCIP Number	B7c6f1d6-d622-4f6c-907b-f4c3173076cb
REACH Regulation	<a href="#">REACH Declaration</a>
Halogen-free status	Halogen free product
PVC free	Yes

### Use Again

 <b>Repack and remanufacture</b>	
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins