



 PRODUCT-DETAILS

S3C-A2

Shunt trip 110...415V



General Information

Extended Product Type	S3C-A2
Product ID	2CDS200982R0002
EAN	4053546116663
Catalog Description	Shunt trip 110...415V
Long Description	Remote opening of the device when a voltage is applied. Suitable for MCBs S 200, S 200 MTR, S 300 P, VY 30, SN 201 series, RCCBs F 200, VY series, RCBOs DS 200, DS 301 C series, SD 200 switch disconnectors series. To be mounted on the right side of the devices.

Technical

Suitable For	S200 S200 M S200 MT S200 MTR S200 P S200 MUC S300 P VY30 SD200 F200
--------------	--

RCCB VY
 SN201
 DS203NC
 S-ARC1
 DS-ARC1
 DSE201 M
 DS201
 DS301C
 S3C-MOD
 F3C-AR
 DS200
 DS202CR
 S200C Enhancement

Suitable for Product Class	Auxiliary switch/relay
Tightening Torque	0.8 N·m
Connecting Capacity	Flexible 0.75 ... 2.5 mm ² Rigid 0.75 ... 2.5 mm ² Stranded 0.75 ... 2.5 mm ²
Wire Stripping Length	7 mm
Terminal Type	Screw Terminals

Electrical

Rated Voltage (U _r)	110 ... 250 V DC 110 ... 415 V AC
Rated Operational Voltage	110 ... 250 DC V 110 ... 415 AC V
Input Voltage Type	AC/DC

Material Compliance

RoHS Declaration	2CDK400627D2701
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20231016
REACH Declaration	9AKK107492A1906
REACH Information	False - does not contain substances > 0.1 mass percentage
REACH Date	20250917
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Storage -40 ... +70 °C
-------------------------	--

Dimensions

Width in Number of Modular Spacings	1.0
Product Net Width	17.4 mm
Product Net Height	85 mm
Product Net Depth / Length	74.1 mm

Product Net Weight	0.062 kg
Dimension Diagram	9AKK108469A5079

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.086 kg
E-Number (Finland)	3217615
E-Number (Norway)	1683230
E-Number (Sweden)	2101487

Certificates and Declarations

Declaration of Conformity - CE	2CDK400627D2701
Declaration of Conformity - UKCA	9AKK108469A1474

Installation

Instructions and Manuals	2CDS207010P0001
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	9AKK108469A4389
-----------------------------------	-----------------

External Classifications and Standards

ETIM 9	EC001286 - Auxiliary device for distribution board devices
ETIM 10	EC001286 - Auxiliary device for distribution board devices
UNSPSC	39121601
eClass	V11.0 : 27143502
IDEA Granular Category Code (IGCC)	4879 >> Shunt release (for power circuit breaker)
Standards	CSA 22.2 No. 235 UL 1077

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs Accessories → Shunt Trips

