



135X3708

FC-302P4K0T5E20H2BGCXXXSXXXALBRCXXXDX

Frequency converter
 FC-302P4K0T5E20H2BGCXXXSXXXALBRCXXXDX
 VLT® AutomationDrive FC-302
 (P4K0) 4.0 KW / 5.0 HP,
 Three phase, 380 - 500 VAC, (E20) IP20 / Chassis
 RFI Filter
 Brake chopper
 Graphical Loc. Cont. Panel
 Coated PCB, No Mains Option
 Latest release std. SW.
 Frame: A2
 PROFINET MCA 120, MCB-102 Encoder Option
 No C1 option, No D option

Other options according to Model code

Model code: FC-302P4K0T5E20H2BGCXXXSXXXALBRCXXXDX

The VLT® AutomationDrive represents a single drive concept that controls the entire range of operations from ordinary to servo like applications on any machine or production line.

[View Efficiency Data](#)

PRODUCT DETAILS

| | | |
|-------------------------------|------|----------------------------|
| Gross weight | | 5.156 Kilogram |
| Net weight | | 4.31 Kilogram |
| Volume | | 21.569 Liter |
| EAN | | 5710108400132 |
| Product View (Switch) | GLBL | Global (Standard) |
| Product Group | FC- | VLT® AutomationDrive FC- |
| Series | 302 | 302 |
| Power Rating | P4K0 | (P4K0) 4.0 KW / 5.0 HP |
| Phase | T | Three phase |
| Mains Voltage | 5 | 380 - 500 VAC |
| Enclosure | E20 | (E20) IP20 / Chassis |
| RFI Filter | H2 | RFI Filter |
| Brake - Safe Stop | B | Brake chopper |
| LCP | G | Graphical Loc. Cont. Panel |
| Coating PCB | C | Coated PCB |
| Mains Option | X | No Mains Option |
| Adaptation A | X | Standard Cable Entries |
| Adaptation B | X | No adaptation |
| Software Release | SXXX | Latest release std. SW. |
| Software Language Pack | X | Standard Language Pack |
| A Option | AL | PROFINET MCA 120 |
| B Option | BR | MCB-102 Encoder Option |
| C0 Option MCO | CX | No C0 option |
| C1 Option | X | No C1 option |

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

PRODUCT DETAILS

| | | |
|--------------------------------------|---------|-------------------------|
| C Option Software | XX | No software option |
| D Option | DX | No D option |
| Frame Size | A2 | A2 |
| Typecode Part 1 | | FC-302P4K0T5E20H2BGC |
| Typecode Part 2 | | XXXSXXXXALBRCXXXDX |
| Product Catalog | NO_VIEW | NO VIEW |
| Power 160% (HO) [KW] | 4 | 4 |
| Height [mm] | 268,0 | 268,0 |
| Width w/ no C options [mm] | 90,0 | 90,0 |
| Width w/ two C options [mm] | 150,0 | 150,0 |
| Depth [mm] | 205,0 | 205,0 |
| Depth with Option A/B [mm] | 220,0 | 220,0 |
| kVA | 6.93 | 6.93 |
| Power Loss HO [W] | 124 | 124 |
| Power Loss HO [W] | 124 | 124 |
| Continuous Current (HO) [A] | 10 | 10 |
| Intermittent Current (HO) [A] | 16 | 16 |
| Continuous Current (HO) [A] | 8.2 | 8.2 |
| Intermittent Current (HO) [A] | 13.1 | 13.1 |
| Calculated Gross Weight [kg] | | 5.156 |
| Calculated Net Weight [kg] | | 4.31 |
| ECCN EU | Y901 | Y901 |
| ECCN US | 3A999.a | 3A999.a |
| Vendor | ERR01 | Cannot Determine Vendor |
| Recommended Factory | ERR01 | Cannot Determine Vendor |
| Modelcode01 | | FC-302P4K0T5E20H2BGC |
| Modelcode02 | | XXXSXXXXALBRCXXXDX |
| Recommended Plant | ERR01 | ERR01 |

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories

**130B0056** [🔗](#)**Adapter Plate, 338x279mm**

With the adapter plate you can replace a VLT® 3000 by a FC drive without having to drill new holes for the FC drive. This makes it easy and fast to replace a VLT® 3000, and as there will be no drilling there will be no swarf harming the electric components.

It is possible to install one or two FC drives in the same place as one VLT® 3000. Or one FC drive with a full size C Option (e.g. MCO305).

The following VLT® 3000 can be mounted on the Adapter Plate 130B0056:

IP00/21: 220/380/500Volt VLT3002-3004 with no brake

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**130B0183** [🔗](#)**Adapter Plate, 395x90mm**

With the adapter plate you can replace a VLT® 5/6/8000 by a FC drive without having to drill new holes for the FC drive. This makes it easy and fast to replace a VLT® 5/6/8000, and as there will be no drilling there will be no swarf harming the electric components.

The following VLT® 5/6/8000 can be mounted on the Adapter Plate 130B0183:

IP20 Book: 200-240Volt VLT5001-5003/VLT6002-6003, 380/500Volt VLT5001-5005, 380-460Volt VLT6002-6005

**130B0184** [🔗](#)**Adapter Plate, 395x130mm**

With the adapter plate you can replace a VLT® 5/6/8000 by a FC drive without having to drill new holes for the FC drive. This makes it easy and fast to replace a VLT® 5/6/8000, and as there will be no drilling there will be no swarf harming the electric components.

The following VLT® 5/6/8000 can be mounted on the Adapter Plate 130B0184:

IP20 Book: 200-240Volt VLT5004-5006/VLT6004-6005, 380/500Volt VLT5006-5011, 380-460Volt VLT6006-6011

**130B0185** [🔗](#)**Adapter Plate, 395x220mm**

With the adapter plate you can replace a VLT® 5/6/8000 by a FC drive without having to drill new holes for the FC drive. This makes it easy and fast to replace a VLT® 5/6/8000, and as there will be no drilling there will be no swarf harming the electric components.

The following VLT® 5/6/8000 can be mounted on the Adapter Plate 130B0185:

IP20 Compact:200-240Volt VLT5001-5006, 380/500Volt VLT5001-5011

IP20/NM1: 200-240Volt VLT6002-6005, 380/460Volt VLT6002-6011, 380-480Volt VLT8006-8011, 550-600Volt VLT 5001-5011, 525-690Volt VLT8002-8011

**130B0295** [🔗](#)**sparepart/terminals accessory bag****130B1022** [🔗](#)**fc-300 spare part/acc. bag a2 +a3 encl.****130B1070** [🔗](#)**RS485 plug, FC series, 10 pcs**

10pcs RS485 connectors for FC-series.

Product group: R

**130B1071** [🔗](#)**6 Pole Connector, FC series, 10 pcs**

6-pole spring cage connectors 10 pcs

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**130B1077** [🔗](#)**Blindcover, w/ Danfoss logo, IP55/66**

LCP Blindcover IP66

**130B1088** [🔗](#)**LCP Blindcover, w/ Danfoss logo, IP20/21****130B1107** [🔗](#)**VLT® Control Panel LCP 102**

Graphic operating unit LCP102 Illuminated graphic display with plain text. Supports all languages and characters. Quick menu for brief commissioning. Saving and copying parameter sets. Online help for each function

**130B1108** [🔗](#)**VLT® 24V DC Supply MCB 107, uncoated**

Connect an external DC supply to keep the control section and any installed option alive during power failure. Enables full operation of the LCP (including the parameter setting) and all installed options without connection to mains.

**130B1113** [🔗](#)**LCP Mounting Kit w/ graphical LCP102, 3m**

The kit includes graphical LCP, fasteners, 3m cable and gasket.

**130B1114** [🔗](#)**LCP Mounting Kit w/ numerical LCP101, 3m**

The kit includes numerical LCP, fasteners, 3m cable and gasket.

**130B1117** [🔗](#)**LCP Mounting Kit, w/ no LCP**

The kit includes fasteners, 3m cable and gasket - There is no LCP included.

**130B1122** [🔗](#)**IP 21/Type 1 conversion kit, A2**

Cover for housing size A2 MCF 101 NEMA1 / IP21

**130B1124** [🔗](#)**VLT® Control Panel LCP 101, numeric**

Numerical control unit for FC 100 and FC 300. Allows access to all device parameters. Quick menu for brief commissioning. Manual / auto switchover and alarm acknowledgment.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**130B1132****IP 21/Type 1 conversion kit, top, A2**

This is only the top part of the kit - If you need a kit with both top and bottom please order 130B1122

**130B1134****VLT® Motion Control MCO 305, uncoated**

Integrated and programmable motion controller for VLT® AutomationDrive FC 301 and FC 302

- Adds additional functionality and flexibility as it is a freely programmable module
- Optimized for all types of positioning and synchronization applications
- Make your own program specially adapted to your application

Contains:

- synchronization (electronic shaft), positioning and electronic cam control
- 2 inputs support both stepwise and absolute encoders
- 1 encoder output (virtual master function)

10 digital inputs

8 digital outputs

- Sends and receives data via fieldbus interface (requires fieldbus Option)
- PC software for programming and commissioning.

Remember to order the Mounting kit if the above MCO option is required retrofitted.

130B7530 - Mounting kit for enclosures A2 and A3

130B7531 - Mounting kit for MCO Option, together with MCB 113, in enclosures A2 and A3.

130B1413 - Mounting kit for enclosure B3

130B1414 - Mounting kit for MCO Option, together with MCB 113, in enclosure B3

130B7532 - Mounting kit for enclosure A5

130B7533 - Mounting kit for all enclosures B, C, D, E and F (B3 excepted)

Danfoss MCO options are not sold without prior advice. Danfoss can offer help with programming / setting up MCO options. Contact Danfoss for advice and prices. Product group: R

**130B1152****VLT® Synchronizing Contr. MCO350, unctd**

Expands the functional properties of the VLT® AutomationDrive in synchronizing applications, and replaces traditional mechanical solutions. Speed synchronizing. Position (angle) synchronizing with or without marker correction. Online adjustable gear ratio. Online adjustable position (angle) offset. Encoder output with virtual master function for synchronization of multiple followers. Control via I/Os or fieldbus. Home function. Configuration as well as read-out of status and data via the Local Control Panel of the drive.

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



130B1153 [🔗](#)

VLT® Position Controller MCO351, unctd

Extends the functional characteristics of the frequency converter in positioning applications

- Direct positioning via fieldbus, relative positioning, absolute positioning and touch probe positioning

- End stop handling (software and hardware)

- Mechanical brake handling (programmable hold delay)

Error handling

- Jog speed / manual operation

- None for programming, as it is pre-programmed

Remember to order the Mounting kit if the above MCO option is required retrofitted.

130B7530 - Mounting kit for enclosures A2 and A3

130B7531 - Mounting kit for MCO Option, together with MCB 113, in enclosures A2 and A3

130B1413 - Mounting kit for enclosure B3

130B1414 - Mounting kit for MCO Option, together with MCB 113, in enclosure B3

130B7532 - Mounting kit for enclosure A5

130B7533 - Mounting kit for all enclosures B, C, D, E and F (B3 excepted)

Danfoss MCO options are not sold without prior advice. Danfoss can offer help with programming / setting up MCO options. Contact Danfoss for advice and prices.

Product group: R



130B1164 [🔗](#)

VLT® Extended Relay Card MCB 113

Adds 7 digital inputs and 2 analog outputs for increased flexibility. 4 SPDT relays. Meets NAMUR recommendations. Galvanic isolation capability.



130B1170 [🔗](#)

LCP Panel Mounting Kit

The kit includes fasteners and gasket. No LCP and no cable included.



130B1208 [🔗](#)

1xMCB 107 24V DC coat w. mount. brackets

Connect an external DC supply to keep the control section and any installed option alive during power failure. Enables full operation of the LCP (including the parameter setting) and all installed options without connection to mains.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**130B1234****VLT® Motion Control MCO 305, coated**

Integrated and programmable motion controller for VLT® AutomationDrive FC 301 and FC 302

- Adds additional functionality and flexibility as it is a freely programmable module
- Optimized for all types of positioning and synchronization applications
- Make your own program specially adapted to your application

Contains:

- synchronization (electronic shaft), positioning and electronic cam control
- 2 inputs support both stepwise and absolute encoders
- 1 encoder output (virtual master function) 10 digital inputs
- 8 digital outputs
- Sends and receives data via fieldbus interface (requires fieldbus option)
- PC software for programming and commissioning Remember to order the Mounting kit if the above MCO option is required retrofitted.

130B7530 - Mounting kit for enclosures A2 and A3

130B7531 - Mounting kit for MCO Option, together with MCB 113, in enclosures A2 and A3

130B1413 - Mounting kit for enclosure B3

130B1414 - Mounting kit for MCO Option, together with MCB 113, in enclosure B3

130B7532 - Mounting kit for enclosure A5

130B7533 - Mounting kit for all enclosures B, C, D, E and F (B3 excepted) Danfoss MCO options are not sold without prior advice.

Danfoss can offer help with programming / setting up MCO options. Contact Danfoss for advice and prices. Product group: R

**130B1252****VLT® Synchronizing Ctrl. MCO 350, ctd**

MCO 350 - synchronous controller Based on the MCO 305 prefabricated controller for Synchronization tasks. The adjustment takes place through parameter settings. Specific Programming skills are not required.

- 2 encoder inputs, both for incremental as well as absolute encoder
 - 1 encoder output (virtual master function)
 - 10 additional digital inputs
 - 8 additional digital outputs
 - fieldbus Communication (requires fieldbus card) with reinforced coating
-

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



130B1253 [🔗](#)

VLT® Position Controller MCO 351, ctd

Extends the functional characteristics of the frequency converter in positioning applications

- Direct positioning via fieldbus, relative positioning, absolute positioning and touch probe positioning

- End stop handling (software and hardware)

- Mechanical brake handling (programmable hold delay)

Error handling

- Jog speed / manual operation

- None for programming, as it is pre-programmed

Remember to order the Mounting kit if the above MCO option is required retrofitted.

130B7530 - Mounting kit for enclosures A2 and A3

130B7531 - Mounting kit for MCO Option, together with MCB 113, in enclosures A2 and A3

130B1413 - Mounting kit for enclosure B3

130B1414 - Mounting kit for MCO Option, together with MCB 113, in enclosure B3

130B7532 - Mounting kit for enclosure A5

130B7533 - Mounting kit for all enclosures B, C, D, E and F (B3 excepted)

Danfoss MCO options are not sold without prior advice.

Danfoss can offer help with programming / setting up MCO options. Contact Danfoss for advice and prices.

Product group: R



130B1264 [🔗](#)

VLT® Extended Relay Card MCB 113, ctd

Adds 7 digital inputs and 2 analog outputs for increased flexibility. 4 SPDT relays. Meets NAMUR recommendations. Galvanic isolation capability.



130B1266 [🔗](#)

VLT MCB 115 Programmable I/O, coated

VLT® MCB 115 programmable I / O, coated



130B5601 [🔗](#)

VLT® DeviceNet converter MCA194 coated

VLT® DeviceNet converter MCA194 coated



130B7145 [🔗](#)

VLT® SALT Controller MCO 360



x10

130B7389 [🔗](#)

NEMA 1 Conversion Kit, Top, 10 pcs, A2

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



130B7531 [🔗](#)

Mounting Kit f. C Option, 60mm, A2/A3

VLT® Mounting kit for enclosure sizes A2 and A3. Must be used when retrofitting 1 pc. of the following MCO options, together with MCB 113 Extended relay card (Located in MCO slot):

- MCO 305 Programmable Motion Controller
- MCO 350 Synchronizing Controller
- MCO 351 Positioning controller
- MCO 360 Salt Controller
- MCO 361 Lift Controller
- Product group: R



130B7635 [🔗](#)

VLT® Lift Controller MCO 361

VLT® Motion Control MCO 305 with special software for lift application

Image coming soon

134B1976 [🔗](#)

Accessory bag for frame A1-A3 w. brake

Image coming soon

134B1992 [🔗](#)

Control Terminals w/ screw connections



134B5223 [🔗](#)

Remote LCP unit, 3m

Remote mounting kit for LCP with cover for outdoor mounting with 3 m (10 ft) cable

Image coming soon

134B5224 [🔗](#)

Remote LCP unit, 5m

Remote mounting kit for LCP with cover for outdoor mounting with 5 m (16 ft) cable

Image coming soon

134B5225 [🔗](#)

Remote LCP unit, 10m

Remote mounting kit for LCP with cover for outdoor mounting with 10 m (33 ft) cable



134B6544 [🔗](#)

Real Time Clock D slot option MCB117

The VLT® Real-time clock option MCB 117 option provides advanced data- logging functionality to the following drives

- VLT® HVAC Drive FC 102
- VLT® Refrigeration Drive FC 103
- VLT® Aqua Drive FC 202
- VLT® Automation Drive FC 301/FC 302

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

Image
coming
soon**134B6883** [🔗](#)**VLT Progr. Contr. MCB 301, coated****175N2584** [🔗](#)**VLT® EtherNet/IP Modbus TCP gateway**Image
coming
soon**175U0009** [🔗](#)**Mounting bracket Kit, 216 x 30 x 18mm**
Mounting angle for flatpack resistor 200W**175U0085** [🔗](#)**Mounting bracket: Footprint, A2**
Back frame A2 for 1 brake resistor**175U0087** [🔗](#)**Mount. Brack. Footprint, A2, f. 2 br.res**
Back frame A2 for 2 brake resistorsImage
coming
soon**175U0388** [🔗](#)**Mounting brackets: Footprint, K3****185B0011** [🔗](#)**FC-302 Demo Case - 120 Vac Supply**

Elevate your sales presentations and on-site training with this high-impact, portable VFD demo kit. Showcasing the Danfoss VLT® FC 302 drive, this suitcase provides a dynamic, hands-on experience for demonstrating the benefits of variable frequency drives in motor control. The integrated flywheel and controls simulate a mechanical load, offering a realistic, visual representation of VFD capabilities. 120VAC Supply (Standard outlet in North America) Dimensions: 24.75 in. x 19.50 in. x 12 in. (63 cm x 50 cm x 30 cm)

**130B1383** [🔗](#)**acc. bag multipack 5 pc frame A2/3**

Krones acc. bag multipack 5pcs for A2/3-frame.

**130B1387** [🔗](#)**5xMCB107 24VDC no coat w.out mount brack**

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

Image coming soon

130B4847 [🔗](#)
extension cable for lcp+communication



134B8492 [🔗](#)
Transducer 0-10g, 4-20mA; HS-22B50



134B8493 [🔗](#)
Transducer 0-25mm/s RMS 4-20mA
 CBM Transducer 0-25mm/s RMS 4-20mA



134B8494 [🔗](#)
Transducer w, temp 0-25mm/s RMS 4-20mA



134B8496 [🔗](#)
CABLE ASSY 10M, STRAIGHT SOCKET CONNETC.

Image coming soon

134B8497 [🔗](#)
Cable assy, M12 female connec.10m screen



134B9400 [🔗](#)
Pressure Sensor 7245T 2x500Pa & PT1000
 DUAL AIR PRESSURE SENSOR ±500PA Temperature drift: ± 0.1% per °C/°F
 Zero point offset: ± 10 % of measuring range
 Above-/below-pressure: max. ± 50 kPa / ± 200 inWC
 Power: 24VAC (± 20%) <0,2W / 15...36VDC
 Operation temperature: -30...+70 °C / -22...+158 °F
 Media temperature -20...+50 °C / -4...+122 °F
 T2-IP65 plastic housing with two M16 cable glands one M12 for temperature
 Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in



134B9401 [🔗](#)
Pressure Sensor 7249T 500/7000Pa & PT1000
 DUAL AIR PRESSURE SENSOR ±500PA Temperature drift: ± 0.1 % per °C # °F
 Zero point offset: ± 10 % of measuring range
 Above- # below-pressure: max. ± 50 kPa / ± 200 inWC
 Power: 24VAC (± 20%) <0,2W / 15...36VDC
 Operation temperature: -30...+70 °C / -22...+158 °F
 Media temperature -20...+50 °C / -4...+122 °F
 T2-IP65 plastic housing with two M16 cable glands one M12 for temperature
 Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**134B9402** [↗](#)**Pressure Sensor 7247T 2x7000Pa & PT1000**

DUAL AIR PRESSURE SENSOR $\pm 7000\text{Pa}$ Temperature drift: $\pm 0.1\%$ per $^{\circ}\text{C}$ #
 $^{\circ}\text{F}$

Zero point offset: $\pm 10\%$ of measuring range

Above- # below-pressure: max. $\pm 50\text{ kPa}$ / $\pm 200\text{ inWC}$

Power: 24VAC ($\pm 20\%$) <0,2W / 15...36VDC

Operation temperature: $-30...+70\text{ }^{\circ}\text{C}$ / $-22...+158\text{ }^{\circ}\text{F}$

Media temperature $-20...+50\text{ }^{\circ}\text{C}$ / $-4...+122\text{ }^{\circ}\text{F}$

T2-IP65 plastic housing with two M16 cable glands one M12 for
 temperature

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

**134B9404** [↗](#)**Pressure Sensor 7225 2x500Pa, Analog**

DUAL AIR PRESSURE SENSOR $\pm 500\text{Pa}$ $\pm 500\text{Pa}$, ANALOGUE

Dual pressure transmitter with 2x8 switchable measuring ranges and 2
 automated analogue output signals in a resistant IP65 plastic housing
 with quick-locking screws, connection nozzles for pressure hose ($\varnothing 6\text{ mm}$)
 and a M16 cable gland for cable connection. The pressure measuring
 transducer automatically detects the required output type and converts
 the measurands into the required standard signal of 0–10 V or 4...20 mA.

Pressure range selection: $\pm 500\text{ Pa} - 0...100\text{Pa} / 200\text{Pa} / 300\text{Pa} / 500\text{Pa}$

Accuracy: 500 Pa typical $\pm 13\text{ Pa}$

Zero point offset: $\pm 10\%$ of measuring range

Above- # below-pressure: max. $\pm 50\text{ kPa}$

Power: 24VAC/DC ($\pm 10\%$) <1,3W,

Output: automatically switching 0 -10 V # 4...20 mA

Working resistance: R_a (ohms) = 25...450 Ohm (at I output)

Load resistance: R_L > 15 kOhm (at U output)

Operation / Media temperature: $-20...+50\text{ }^{\circ}\text{C}$ / $-4...+122\text{ }^{\circ}\text{F}$

T2-IP65 plastic housing with one M16 cable gland

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**134B9405****Pressure Sensor 7229 500/7000Pa, Analog**DUAL AIR PRESSURE SENSOR $\pm 500\text{Pa}$ $\pm 7000\text{Pa}$, ANALOGUE

Dual pressure transmitter with 2x8 switchable measuring ranges and 2 automated analogue output signals in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose (\varnothing 6 mm) and a M16 cable gland for cable connection. The pressure measuring transducer automatically detects the required output type and converts the measurands into the required standard signal of 0–10 V or 4...20 mA. Pressure range selection: $\pm 500\text{ Pa} - 0 \dots 100\text{Pa} / 200\text{Pa} / 300\text{Pa} / 500\text{Pa}$ Pressure range selection: $\pm 7000\text{ Pa} - 0 \dots 1000\text{Pa} / 2000\text{Pa} / 3000\text{Pa} / 5000\text{Pa} / 7000\text{Pa}$

Accuracy: 500 Pa typical $\pm 13\text{ Pa}$ Accuracy: 7000 Pa typical $\pm 105\text{ Pa}$ Zero point offset: $\pm 10\%$ of measuring rangeAbove- # below-pressure: max. $\pm 50\text{ kPa}$ Power: 24VAC/DC ($\pm 10\%$) <1,3W,

Output: automatically switching 0 -10 V # 4...20 mA

Working resistance: R_a (ohms) = 25...450 Ohm (at I output)Load resistance: R_L > 15 kOhm (at U output)Operation / Media temperature: $-20 \dots +50\text{ }^\circ\text{C} / -4 \dots +122\text{ }^\circ\text{F}$

T2-IP65 plastic housing with one M16 cable gland

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

**134B9406****Pressure Sensor 7227 2x7000Pa, Analog**DUAL AIR PRESSURE SENSOR $\pm 7000\text{Pa}$ $\pm 7000\text{Pa}$, ANALOGUE

Dual pressure transmitter with 2x8 switchable measuring ranges and 2 automated analogue output signals in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose (\varnothing 6 mm) and a M16 cable gland for cable connection. The pressure measuring transducer automatically detects the required output type and converts the measurands into the required standard signal of 0–10 V or 4...20 mA.

Pressure range selection: $\pm 7000\text{ Pa} - 0 \dots 1000\text{Pa} / 2000\text{Pa} / 3000\text{Pa} / 5000\text{Pa} / 7000\text{Pa}$ Accuracy: 7000 Pa typical $\pm 105\text{ Pa}$ Zero point offset: $\pm 10\%$ of measuring rangeAbove- # below-pressure: max. $\pm 50\text{ kPa}$ Power: 24VAC/DC ($\pm 10\%$) <1,3W,

Output: automatically switching 0 -10 V # 4...20 mA

Working resistance: R_a (ohms) = 25...450 Ohm (at I output)Load resistance: R_L > 15 kOhm (at U output)Operation / Media temperature: $-20 \dots +50\text{ }^\circ\text{C} / -4 \dots +122\text{ }^\circ\text{F}$

T2-IP65 plastic housing with one M16 cable gland

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**134B9407****Airflow Sensor KFTF Temp & Humidity**

DUCT HUMIDITY- AND TEMPERATURE SENSORS KFTF-MB

Calibratable duct humidity and temperature sensor KFTF-T3 ($\pm 2.0\%$) with Modbus RTU connection, in a resistant IP65 plastic housing with quick-locking screws and M16 cable gland for cable connection and a plastic sinter filter (exchangeable). Including mounting flange to detect the relative humidity (0...100% RH) and the temperature ($-35...+80\text{ }^{\circ}\text{C}$) inside a tube, including various parameters in the humidity measurement. The duct sensor is applied in a non-aggressive and dust-free environment and is suitable for installation in ceilings, ducts and devices.

International SI units (default) can be switched to Imperial (via Modbus).

Measuring range: 0...100 % RH (humidity) / $-35...+80\text{ }^{\circ}\text{C}$ (temperature)

Medium: clean air and non-aggressive, non-combustible gases

Deviation, humidity: typical $\pm 2.0\%$ (20...80 % RH) at $+25\text{ }^{\circ}\text{C}$, otherwise $\pm 3.0\%$

Deviation, temperature: typical $\pm 0.2\text{ K}$ at $+25\text{ }^{\circ}\text{C}$

Zero point offset: $\pm 10\%$ RH (humidity) / $\pm 5\text{ }^{\circ}\text{C}$ (temperature)

Power: 24VAC ($\pm 20\%$) / 15...36VDC - 24DC <1,2W

Operation temperature: $-30...+70\text{ }^{\circ}\text{C}$ / $-22...+158\text{ }^{\circ}\text{F}$

T3-IP65 plastic housing with two M20 cable glands

Housing dimensions: 108 x 78.5 x 43.3 mm / 4.25 x 3.1 x 1.7 in

Image
coming
soon**134B9408****Airflow Sensor 8148 Temp&Humidity&500Pa**DUCT HUMIDITY-, TEMPERATURE- AND PRESSURE SENSORS $\pm 500\text{Pa}$ -MB

Maintenance-free duct sensor covering humidity, temperature and pressure in one transducer. Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws and M16 cable gland for cable connection. Including mounting flange to detect the relative humidity (0...100% RH) and the temperature ($-35...+80\text{ }^{\circ}\text{C}$) inside a tube, with an exchangeable plastic sinter filter. A differential air pressure (max. $\pm 500\text{ Pa}$) with connection nozzles for pressure hose ($\varnothing 6\text{ mm}$). The duct sensor is applied in a non-aggressive and dust-free environment and is suitable for installation in ceilings, ducts and devices. International SI units (default) can be switched to Imperial (via Modbus).

Measuring range: 0...100 % RH (humidity) / $-35...+80\text{ }^{\circ}\text{C}$ / $-31... +176\text{ }^{\circ}\text{F}$ (temperature)

Medium: clean air and non-aggressive, non-combustible gases
Deviation, humidity: typical $\pm 2.0\%$ (20...80 % RH) at $+25\text{ }^{\circ}\text{C}$ / $+77\text{ }^{\circ}\text{F}$, otherwise $\pm 3.0\%$
Deviation, temperature: typical $\pm 0.2\text{ K}$ at $+25\text{ }^{\circ}\text{C}$ / $\pm 0.4\text{ }^{\circ}\text{F}$ at $+77\text{ }^{\circ}\text{F}$

Pressure range: $\pm 500\text{ Pa}$

Accuracy: 500 Pa/2.0 inWC: typical $\pm 13\text{ Pa}$ at $+25\text{ }^{\circ}\text{C}$ / $\pm 0.05\text{ inWC}$ at $+77\text{ }^{\circ}\text{F}$ Above- #

below-pressure: max. $\pm 50\text{ kPa}$ Power: 24VAC ($\pm 20\%$) / 15...36VDC - 24DC <0,2W

Operation temperature: $-30...+70\text{ }^{\circ}\text{C}$ / $-22...+158\text{ }^{\circ}\text{F}$

Media temperature $-20...+50\text{ }^{\circ}\text{C}$ / $-4...+122\text{ }^{\circ}\text{F}$ IP65 plastic housing two M16 cable glands

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

Image
coming
soon**134B9409****Airflow Sensor 8147 Temp&Humidity&7000Pa**

DUCT HUMIDITY-, TEMPERATURE- AND PRESSURE SENSORS ±7000PA-MB

Maintenance-free duct sensor covering humidity, temperature and pressure in one transducer. Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws and M16 cable gland for cable connection. Including mounting flange to detect the relative humidity (0...100% RH) and the temperature (-35...+80 °C) inside a tube, with an exchangeable plastic sinter filter. A differential air pressure (max. ± 7000 Pa) with connection nozzles for pressure hose (Ø 6 mm). The duct sensor is applied in a non-aggressive and dust-free environment and is suitable for installation in ceilings, ducts and devices. International SI units (default) can be switched to Imperial (via Modbus).

Measuring range: 0...100 % RH (humidity) / - 35...+80°C / -31... +176°F (temperature)

Medium: clean air and non-aggressive, non-combustible gases Deviation,

humidity: typical ± 2.0 % (20...80 % RH) at +25°C/+77°F, otherwise ± 3.0 % Deviation,

temperature: typical ± 0.2 K at +25 °C / ± 0.4 °F at +77 °F Pressure range: ± 7000 Pa

Accuracy: 7000 Pa/28 inWC: typical ± 105 Pa at +25 °C / ± 0.12 inWC at + 77 °F Above- #

below-pressure: max. ± 50 kPa

Power: 24VAC (± 20%) / 15...36VDC - 24DC <0,2W

Operation temperature: -30...+70 °C / -22...+158 °F Media temperature -20...+50 °C / -4...+122 °F

IP65 plastic housing two M16 cable glands

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

**134B9410****Wall Sensor ATM2 Temperature**

OUTSIDE / WET ROOM TEMPERATURE SENSOR ATM2-MB

Calibratable outside temperature sensor ATM2, PT1000 measure temperature (-50...+150 °C), with Modbus RTU connection, in a resistant IP65 plastic housing with quick-locking screws and M20 cable gland for cable connection. International SI units (default) can be changed to imperial (via Modbus).

Sensor type: PT1000 class B (DIN EN 60751)

Measuring range: - 50...+150°C / -31... +176°F

Deviation: typical ± 0.2 K at +25 °C / ± 77 °F

Zero point offset: ± 10 °C / ± 50 °F

Ambient temperature: Measuring transducer -30...+70 °C / -22... +158°F

Medium: clean air and non-aggressive, non-combustible gases

Power: 24VAC (± 20%) / 15...36VDC - 24DC <1,2W

Operation temperature: -30...+70 °C / -22...+158 °F

T3-IP65 plastic housing with two M20 cable glands

Housing dimensions: 108 x 78.5 x 43.3 mm / 4.25 x 3.1 x 1.7 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**134B9411** **Wall Sensor AFTF Temp & Humidity**

ON-WALL- HUMIDITY- AND TEMPERATURE SENSORS AFTF-MB

Calibratable outside humidity and temperature sensor AFTF, detect the relative humidity (0...100% RH) and the temperature (-35...+80 °C), including various parameters in the humidity measurement. Applied in clean air and non-aggressive, dust-free environment. With a Modbus connection in a resistant IP65 plastic housing and M20 cable gland for cable connection, with quick-locking screws and an exchangeable plastic sinter filter. International SI units (default) can be changed to imperial (via Modbus).

Measuring range: 0...100 % RH (humidity) / - 35...+80 °C (temperature)

Medium: clean air and non-aggressive, non-combustible gases
 Deviation, humidity: typical ± 2.0 % (20...80 % RH) at +25 °C, otherwise ± 3.0 % Deviation,
 temperature: typical ± 0.4 K at +25 °C / ± 77 °F

Zero point offset: ± 10 % RH (humidity) / ± 5 °C (temperature)

Power: 24VAC (± 20 %) / 15...36VDC - 24DC <1,2W

Operation temperature: -30...+70 °C / -22...+158 °F T3-IP65 plastic housing with two M20 cable glands

Housing dimensions: 108 x 78.5 x 43.3 mm / 4.25 x 3.1 x 1.7 in

**134B9412** **Airflow Sensor TF65 PT1000 Temperature**

DUCT TEMPERATURE SENSOR TF 65

The TF 65 temperature measuring transducer is a PT1000 class B resistance sensor with passive output. Measuring range from -30...+150 °C. In a resistant IP67 plastic housing and M16 cable gland for cable connection and a straight protective measuring tube and a mounting flange.

Sensor type: PT1000 class B (DIN EN 60751) 1000ohm at 0°C $\pm 0,3$ K

Measuring range: -30...+150 °C / -22...+302 °F

Ambient temperature: -20...+100 °C / -4...+212 °F

Testing current: < 0.6 mA

Insulating resistance: 100 M#, at +20 °C (500V DC)

Connection type: 2-wire connection

Measuring tube: stainless steel, V4A (1.4571), \varnothing 6 mm, inserted length = 300 mm / 11.8 in

T1-IP67 plastic housing with a M16 cable glands and a mounting flange.

Housing dimensions: 72 x 64 x 37.8 mm / 2.83 x 2.52 x 1.49 in

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**134B9413** **Airflow Sensor KLQ CO2 & Air Quality**

DUCT AIR QUALITY (VOC) AND CO2 SENSOR KLQ-CO2-MB

Maintenance-free duct sensor covering air quality (VOC 0...100 %), carbon dioxide (CO2 0...5000 ppm) and atmospheric pressure (hPa). The air quality is detected by a VOC sensor (mixed gas sensor for volatile organic substances) and include an automatic calibration. It determines the loading of the room air due to contaminated gases such as cigarette smoke, body perspiration, exhaled breathing air, solvent vapors, emissions etc. The air contamination can be selected into different sensitivity ranges as low, medium or high. The CO2 measurement is performed using an optical NDIR sensor (non-dispersive infra-red technology), and the detection range is calibrated for standard applications such as monitoring residential rooms and conference rooms. A microprocessor-controlled solution with factory sensor calibration, Modbus RTU connection in a resistant IP65 plastic housing with mounting flange, quick-locking screws and two M16 cable gland for cable connection. International SI units (default) can be changed to imperial (via Modbus).

VOC Sensor: Volatile Organic Compounds sensor (metal oxide) with automatic calibration

VOC measuring range: 0...100 % air quality; referred to calibrating gas

temperature dependence: ± 5 ppm pro $^{\circ}\text{C}$ or $\pm 0,5$ % of measured value pro

$^{\circ}\text{C}$ (whichever is higher) pressure dependence: ± 0.13 % per mm Hg

Medium: clean air and non-aggressive, non-combustible gases

Power: 24VAC/DC ($\pm 10\%$) 24DC <1,6W

Operation temperature: $-10...+60$ $^{\circ}\text{C}$ / $14...+140$ $^{\circ}\text{F}$

T2-IP65 plastic housing two M20 cable glands

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**134B9414** **Antifreeze Thermostat FS20, 0/+15C**

TWO-PHASE FROST PROTECTION THERMOSTATS FS-20-UW

Electronic frost protection thermostat or frost monitor with switching relay output, continuous temperature and valve output (summation output 0–10 V) and control and cascading output (0–10 V), optionally with connection for a heating element. A IP65 resistant plastic housing with display with the actual temperature, measuring range, overrange/underrange of the set switch point (frost protection temperature) and alarm indicator for "frost" or "error" (capillary breakage, overvoltage/undervoltage), quick locking screws and a fully active sensor rod made of copper. The delivery scope includes a set of MK-05-K mounting clamps for expert attachment of the sensor rod.

Measuring range: 0...+15 °C / 32...+59 °F

Accuracy: typical ± 1 K (at +10 °C)

Sensor type: 3m Copper rod active along the entire sensor length, min. response length of 25 cm

Input: 1 x 0 -10 V control input DDC 1 x 0 -10 V output valve (frost signal with control voltage and cascading) 1 x potential-free changeover contact (24 V), range of adjustment 0...+ 15 °C

Current consumption: max. 100 mA at 24 V DC Load resistance: RL > 50 kOhm

Ambient temperature: -15...+50 °C / 5...+122 °F (Housing) -20...+60 °C / -4...+140 °F Sensor and capillary tube > 20 cm from the housing.

Power: 24VAC/DC (± 10%) 24DC < 2,4W T2-IP65 plastic housing with three-line display 70x40 mm (WxH), a M16 cable glands and MK-05-K mounting clamps.

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

**175Z0929** **LCP Cable, 3m**

Cable for control panel (LCP), 3 meters Works with the following LCP:

Alphanumeric control panel LCP3 - 175N0131

VLT® LCP 102 Graphic Display - 130B1107

VLT® LCP 101 Numeric Display - 130B1124

VLT® LCP 102 Graphic display IP66 - 130B1078

Product group: F1

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.