

**060G6240****Pressure transmitter, MBS 3000, 0 bar - 40 bar, 0 psi - 580 psi**

Pressure reference: Sealed gauge, Output signal: Current, Electrical
connection: M12 x 1, Pressure connection type: G, Pressure connection size:
1/2, Specification key: MBS 3000-2631-E3AB08-0

PRODUCT DETAILS

Gross weight	0.18 Kilogram
Net weight	0.164 Kilogram
Volume	0.256 Liter
EAN	5702428831970
Type	MBS 3000
Product group	Sensors
Product Name Description	Pressure transmitter
+ supply	Pin 1
- common	Pin 4
Accuracy, max. [±FS%]	1 %
Accuracy, typical [±FS%]	0.5 %
Adj. zero point and span	No
Ambient temperature range [°C] [max]	85 °C
Ambient temperature range [°C] [min]	-25 °C
Ambient temperature range [°F] [max]	185 °F
Ambient temperature range [°F] [min]	-13 °F
CE evaluated	Yes
China RoHS compliance	Out of scope
Compensated temp. range [°C] [max]	80 °C
Compensated temp. range [°C] [min]	0 °C
Compensated temp. range [°F] [max]	176 °F
Compensated temp. range [°F] [min]	32 °F
Contains batteries	No
EEE category	5 small equipment (any external dimension < 50 cm)
Electrical conn. Male/Female	Male
Electrical connection	M12 x 1
Electrical connection size	4 pin
Electrical connection standard	IEC 61076-2-101
Enclosure rating IP	IP67
EU RoHS compliance	Yes with exemptions

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Pressure transmitter, MBS 3000, 0 bar - 40 bar, 0 psi - 580 psi
PRODUCT DETAILS

EU RoHS exemption clause	6(c)
Flush diaphragm	No
High Clipping Level	22.4
In scope of WEEE	Yes
International Article Number	5702428831970
Intrinsically safe	No
Low Clipping level	3.6
Medium temperature range [°C] [max]	85 °C
Medium temperature range [°C] [min]	-40 °C
Medium temperature range [°F] [max]	185 °F
Medium temperature range [°F] [min]	-40 °F
Non-linearity BFSL [±FS%]	0.5 %
Output signal	Current
Output signal [mA] [max]	20 mA
Output signal [mA] [min]	4 mA
Overload pressure max. [bar]	240 bar
Packing format	Multi pack
Pressure connection HEX [mm]	27 mm
Pressure connection size	1/2
Pressure connection standard	EN 837
Pressure connection type	G
Pressure Male/Female	Male
Pressure range [bar] [max]	40 bar
Pressure range [bar] [min]	0 bar
Pressure range [psi] [max]	580 psi
Pressure range [psi] [min]	0 psi
Pressure reference	Sealed gauge
Pulse-snobber	No
Quantity per packing format	20 pc
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Response time max. [ms]	4 ms
SCIP dossier no.	16d2efc6-64f3-4a4e-ae98- a3fd7ce0218d
SCIP dossier product name	AKS/MBS
Specification key	MBS 3000-2631-E3AB08-0
Supply voltage [V] DC [max]	32 V
Supply voltage [V] DC [min]	9 V
UL evaluated	Yes

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories

We're sorry, but the requested information is currently unavailable.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

**Accessories**

This may be because accessories for this product are not available or the data is incomplete.

For the latest and most accurate information, please visit store.danfoss.com.

Thank you for your understanding.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.