



## MY4-GS-R AC48

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 48 VAC

# Specifications

<b>Mounting method</b>	With plug-in socket
<b>Usage</b>	General purpose
<b>Poles</b>	4
<b>Rated carry current</b>	6 A
<b>Coil voltage</b>	48 V
<b>Operation voltage</b>	AC
<b>Contact material</b>	Ag
<b>Contact description</b>	4PDT
<b>Features</b>	Transparent case, With mechanical indicator
<b>Terminal type</b>	Plug-in, Solder

# Fits to



## PY14-02

Socket, back-connecting, 14-pin, PCB terminals



## PYF-14-PU

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals



## PYF-14-PU-L

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals,



## PYF14-ESN-B

Socket, with common and coil terminals on the bottom and with the NC & NO terminal on the top - Black.



## PYF14-ESS-B

Socket, with coil terminals on the bottom and with the common and NC & NO terminals on the top - Black.



## PYF14A-N

Socket, DIN rail/surface mounting, 14-pin, screw terminals (IEC/VDE)



## PYF14S

Socket, DIN rail mounting, 14-pin, screwless terminals



## PYFZ-14-E

Socket, DIN rail/surface mounting, 14-pin, screw terminals (standard)

# Downloads



## EAC Mark removal Discontinuation Notice

EN PDF 221 KB



## Industrial Relays Brochure

EN PDF 2.77 MB



## MY-GS- R/MY(s)/MYK/MYQ/MYH Miniature Power Relays

Datasheet

EN PDF 20.2 MB



## OMRON Manufacturing Know-How: High Quality Relays

Leaflet

EN PDF 449 KB



## Solution case study No.8 Environment resistance

Brochure

EN PDF 623 KB

