

# Product datasheet

Specifications



## PM5320 Meter, ethernet, up to 31st H, 256K 2DI/2DO 35 alarms

Local distributor code:

398144432

METSEPM5320

EAN Code: 3606480614019

### Main

Range	PowerLogic
Product name	PowerLogic PM5000
Device short name	PM5320
Product or component type	Power meter

### Complementary

Power quality analysis	up to the 31st harmonic
Device application	Multi-tariff Power monitoring
Type of measurement	Current Voltage Frequency Power factor Energy Active and reactive power
supply voltage	90...450 V AC 45...65 Hz 100...300 V DC
Network frequency	50 Hz 60 Hz
[In] rated current	1 A 5 A
type of network	1P + N 3P + N 3P
Maximum power consumption in VA	11 VA at 415 V
Ride-through time	80 ms 120 V AC typical 100 ms 230 V AC typical 100 ms 415 V AC typical 50 ms 125 V DC typical
Display type	Monochrome graphic LCD
Display resolution	128 x 128 pixels
Sampling rate	64 samples/cycle
Measurement current	5...8500 mA
Analogue input type	Voltage (impedance 5 MOhm) Current (impedance <= 0.3 mOhm)
Measurement voltage	35...760 V AC 45...65 Hz between phases 20...440 V AC 45...65 Hz between phase and neutral
Frequency measurement range	45...65 Hz
Number of inputs	2 digital

<b>Measurement accuracy</b>	Active energy +/- 0.5 % Reactive energy +/- 2 % Active power +/- 0.5 % Apparent power +/- 0.5 % Frequency +/- 0.05 % Power factor +/- 0.5 Current +/- 0.5 % Voltage +/- 0.5 % Apparent energy +/- 0.5 % Reactive power +/- 2 %
<b>Accuracy class</b>	Class 0.5S active energy conforming to IEC 62053-22
<b>Number of outputs</b>	2 digital
<b>Information displayed</b>	Tariff (4)
<b>Communication port protocol</b>	Modbus TCP/IP at 10/100 Mbit/s, insulation 2500 V BACnet IP
<b>Communication port support</b>	ETHERNET
<b>Data recording</b>	Maintenance logs Alarm logs Min/max of instantaneous values Event logs Time stamping Data logs
<b>Memory capacity</b>	256 kB
<b>Connections - terminals</b>	Voltage circuit: screw terminal block4 Control circuit: screw terminal block2 Current transformer: screw terminal block6 Input/output circuit: screw terminal block6 Relay output: screw terminal block4 Ethernet network: RJ45 connector
<b>Mounting mode</b>	Flush-mounted
<b>Mounting support</b>	Framework
<b>Standards</b>	IEC 62053-22:2020 EN 50470-1 IEC 60529 IEC 61557-12:2015 UL 61010-1 EN 50470-3 IEC 62053-24 IEC 62053-23:2020 IEC 62052-11:2020 IEC 62052-31:2015
<b>Product certifications</b>	CE conforming to IEC 61010-1 CULus conforming to UL 61010-1
<b>Width</b>	96 mm
<b>Depth</b>	72 mm
<b>Height</b>	96 mm
<b>Net weight</b>	430 g

## Environment

<b>Electromagnetic compatibility</b>	<p>Limitation of voltage changes, voltage fluctuations and flicker in low-voltage class A conforming to IEC 61000-3-3</p> <p>Electrostatic discharge - test level: 8 kV level 4 conforming to IEC 61000-4-2</p> <p>Radiated radio-frequency electromagnetic field immunity test level 3 conforming to IEC 61000-4-3</p> <p>Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4</p> <p>Surge immunity test level 4 conforming to IEC 61000-4-5</p> <p>Voltage dips and interruptions immunity test class A conforming to IEC 61000-4-11</p> <p>Limits for harmonic current emissions class A conforming to IEC 61000-3-2</p> <p>Conducted RF disturbances level 3 conforming to IEC 61000-4-6</p> <p>Magnetic field at power frequency level 4 conforming to IEC 61000-4-8</p> <p>Conducted and radiated emissions class B conforming to EN 55022</p> <p>Limitation of voltage changes, voltage fluctuations and flicker in low-voltage level 4 conforming to IEC 61000-3-3</p> <p>Radiated radio-frequency electromagnetic field immunity test class B conforming to IEC 61000-4-3</p>
<b>IP degree of protection</b>	<p>IP54 display: conforming to IEC 60529</p> <p>IP30 rear: conforming to IEC 60529</p>
<b>Relative humidity</b>	5...95 % at 50 °C non-condensing
<b>Pollution degree</b>	2
<b>Ambient air temperature for operation</b>	<p>-25...70 °C meter</p> <p>-20...70 °C display</p> <p>-25...-20 °C (with reduced performance) display</p>
<b>Ambient air temperature for storage</b>	-40...85 °C
<b>Operating altitude</b>	<p>2000 m CAT III</p> <p>3000 m CAT II</p>

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	11.500 cm
<b>Package 1 Width</b>	12.600 cm
<b>Package 1 Length</b>	12.600 cm
<b>Package 1 Weight</b>	472.000 g
<b>Unit Type of Package 2</b>	S03
<b>Number of Units in Package 2</b>	12
<b>Package 2 Height</b>	30.000 cm
<b>Package 2 Width</b>	30.000 cm
<b>Package 2 Length</b>	40.000 cm
<b>Package 2 Weight</b>	6.306 kg
<b>Unit Type of Package 3</b>	P06
<b>Number of Units in Package 3</b>	96
<b>Package 3 Height</b>	75.000 cm
<b>Package 3 Width</b>	60.000 cm
<b>Package 3 Length</b>	80.000 cm
<b>Package 3 Weight</b>	61.340 kg

## Logistical informations

<b>Country of origin</b>	IN
--------------------------	----

## Contractual warranty



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint 222

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 2869ba20-8929-483b-9301-6e9169536ade

REACH Regulation [REACH Declaration](#)

## Use Again

### Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins