

Product datasheet

Specifications



APC Smart-UPS On-Line,
2200VA, Lithium-ion, Rackmount
4U, 230V, 6x C13+2x C19 IEC
outlets, SmartSlot, Extended long
runtime, Rail kit included

SRTL2200RM4UXLI

EAN Code: 0731304508977

Overview

| | |
|--------------|-----------------------------------------------------------------------------|
| Presentation | High density, double-conversion on-line power protection with long runtime. |
| Lead time | Usually in Stock |

Main

| | |
|---------------------------|------------------------------------|
| Main Input Voltage | 230 V AC 1 phase |
| Product or component type | Uninterruptible power supply (UPS) |
| Other Input Voltage | 220 V |
| Main Output Voltage | 230 V AC 1 phase |
| Other Output Voltage | 220 V |
| Rated power in W | 1980 W |
| rated power in VA | 2200 VA |
| Input Connection Type | IEC 60320 C20 |
| output connection type | 6 IEC 60320 C13 |
| Number of rack unit | 4U |
| Cable length | 1.8 m |
| Number of cables | 1 |
| Range of product | Smart-UPS On-Line |

Complementary

| | |
|------------------|----------------------------------------|
| Battery type | Li-Ion (Lithium-Ion) internal included |
| UPS connectivity | Serial port USB port |
| Mounting mode | Rack-mounted with included kit |

Batteries & Runtime

| | |
|--------------------------------|---------------------------------------|
| Run Time | View Runtime Graph |
| Efficiency | View Efficiency Graph |
| Battery type | Li-Ion (Lithium-Ion) |
| Battery voltage | 48 V |
| Extended runtime | 1 |
| Number of battery filled slots | 0 |

| | |
|------------------------------|----------------|
| Number of battery free slots | 0 |
| Battery life | 5...10 year(s) |
| Battery charger power | 158 W rated |

General

| | |
|-------------------------------------|--------------------------|
| Number of power module filled slots | 0 |
| Number of power module free slots | 0 |
| product web sub-family | Lithium-Ion |
| Redundant | No |
| UPS type | Double conversion online |

Physical

| | |
|---------------------|-------------------------------|
| Colour | Black with silver front bezel |
| Height | 171 mm |
| Width | 432 mm |
| Depth | 639 mm |
| Net weight | 43.2 kg |
| Mounting preference | No preference |
| Mounting mode | Rack-mounted with kit |
| Two post mountable | 0 |
| USB compatible | Yes |
| Mounting position | Horizontal Vertical |

Input

| | |
|----------------------|-------------------------|
| Input voltage limits | 160...275 V |
| Network frequency | 40...70 Hz auto-sensing |

Output

| | |
|----------------------------------|---------------------------------|
| Bypass type | Built-in bypass |
| Crest factor | 3 : 1 |
| Harmonic distortion | Less than 2 % |
| Maximum configurable power in VA | 2200 VA |
| Maximum configurable power in W | 1980 W |
| Wave type | Sine wave |
| Output frequency | 50/60 Hz +/- 3 Hz sync to mains |

Conformance

| | |
|------------------------|---------------|
| Product certifications | CE UK PSTI |
| Marking | CE Mark |

Environmental

| | |
|---------------------------------------|-------------------------|
| Acoustic level | 50 dBA |
| Heat dissipation | 317 Btu/h |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for operation | 0...40 °C |
| Ambient air temperature for storage | -20...50 °C |
| Storage altitude | 0...15240 m |
| IP degree of protection | IP20 |
| Relative humidity | 0...95 % non-condensing |
| Storage Relative Humidity | 0...95 % non-condensing |

Communications & Management

| | |
|---------------------|------------------------------------------------------|
| Emergency power off | Yes |
| Free slots | 1 |
| Alarm | Audible and visible alarms : prioritized by severity |

Surge Protection and Filtering

| | |
|-------------------|-------|
| Surge energy rate | 432 J |
|-------------------|-------|

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 24.5 cm |
| Package 1 Width | 60 cm |
| Package 1 Length | 81 cm |
| Package 1 Weight | 56.5 kg |

Contractual warranty

| | |
|----------------------|----|
| Warranty (in months) | 60 |
|----------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant with Exemptions

REACH Regulation

[REACH Declaration](#)

Energy efficiency

Energy Efficiency Optimized

Energy efficient product

Use Again

Repack and remanufacture

End of life manual availability

[End of Life Information](#)

Removable battery

User replaceable

Take-back

No

WEEE Label


 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative







