

**084Z7259** [🔗](#)**Sensor pocket, MBT 120**

Protection tube diameter [mm]: 11, Insertion length [mm]: 100, Process connection type: G, 1/2, Temperature range [°C]: -50 - 200, Protection tube material: AISI 316 Ti, Used for product: MBT 3560, MBT 5560

**PRODUCT DETAILS**

<b>Gross weight</b>	0.108 Kilogram
<b>Net weight</b>	0.104 Kilogram
<b>Volume</b>	0.108 Liter
<b>EAN</b>	5702423201396
<b>Type</b>	MBT 120
<b>Product group</b>	Accessories, sensors
<b>Product Name Description</b>	Sensor pocket
<b>Approval</b>	CE
<b>CE evaluated</b>	Yes
<b>China RoHS compliance</b>	Out of scope
<b>Connection material</b>	AISI 316 Ti
<b>Connection standard</b>	ISO 228
<b>Connection type</b>	G
<b>Contains batteries</b>	No
<b>EEE category</b>	5 small equipment (any external dimension < 50 cm)
<b>EU RoHS compliance</b>	Yes
<b>EU RoHS exemption clause</b>	No
<b>In scope of WEEE</b>	Yes
<b>Insertion length [in]</b>	3.94 in
<b>Insertion length [mm]</b>	100 mm
<b>Insertion type</b>	Fixed
<b>Packing format</b>	Multi pack
<b>Process connection Male/Female</b>	Male
<b>Process connection material</b>	AISI 316 Ti
<b>Process connection size</b>	1/2
<b>Process connection standard</b>	ISO 228-1-A
<b>Process connection type</b>	G
<b>Protection tube diameter [in]</b>	0.433 in
<b>Protection tube diameter [mm]</b>	11 mm
<b>Protection tube material</b>	AISI 316 Ti
<b>Quantity per packing format</b>	20 pc
<b>REACH Candidate List substances</b>	No
<b>Temperature range [°C] [max]</b>	200 °C
<b>Temperature range [°C] [min]</b>	-50 °C
<b>Temperature range [°F] [max]</b>	392 °F
<b>Temperature range [°F] [min]</b>	-58 °F
<b>Type designation</b>	MBT 120-630-100-3

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



---

**PRODUCT DETAILS**

---

<b>UL evaluated</b>	Out of scope
<b>Used for product</b>	MBT 3560, MBT 5560

---

**For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [↗](#)**

---

**Accessories**

**We're sorry, but the requested information is currently unavailable.**

This may be because accessories for this product are not available or the data is incomplete.

For the latest and most accurate information, please visit [store.danfoss.com](https://store.danfoss.com).

Thank you for your understanding.

---

**For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)**

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.