



SIMATIC ET 200SP HA, holder module IM single, support for holding one interface module of the ET 200SP HA, including one server module

General information	
Product type designation	IM carrier module, single
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; Asset data
Supply voltage	
Rated value (DC)	24 V
Hardware configuration	
Slots	
<ul style="list-style-type: none"> <li>Number of slots</li> </ul>	1
Potential separation	
between backplane bus and supply voltage	Yes
Isolation	
Isolation tested with	1 500 V DC/1 min, type test
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>horizontal installation, min.</li> <li>horizontal installation, max.</li> <li>vertical installation, min.</li> <li>vertical installation, max.</li> </ul>	-40 °C 70 °C -40 °C 60 °C
Dimensions	
Width	100 mm
Height	141 mm
Depth	35 mm; measured without power plug
Weights	
Weight, approx.	165 g; measured without power plug

Classifications			
		Version	Classification
	eClass	14	27-24-26-07
	eClass	12	27-24-26-07
	eClass	9.1	27-24-26-07
	eClass	9	27-24-26-07
	eClass	8	27-24-26-07
	eClass	7.1	27-24-26-07
	eClass	6	27-24-26-07
	ETIM	10	EC001603
	ETIM	9	EC001603
	ETIM	8	EC001603

## Approvals / Certificates

## General Product Approval



[Declaration of Con-  
formity](#)



## For use in hazardous locations



IECEX

[Miscellaneous](#)

last modified:

10/23/2025