

SIMATIC process control system IPC547J; (rack PC, 19, 4 U), interfaces: 3x Gbit LAN (RJ45), 1x DVI-D, 2x display port; 1x COM, audio; 6x USB 3.1 Gen. 2 (2x type C, 4x type A) on the rear side, 2x USB3.1 Gen.1 (type A) on the front, 2x USB 2.0 internal; 7 slots: 5x PCIe, 2x PCI, internal, temperature and fan monitoring watchdog, card retainer; Xeon W-1270E (8C/16T, 3.4 (4.8) GHz, 16 MB cache), MB (Chipset W480E), iAMT, PCS 7 OS server RAID1, 2x 2 TB HDD [Enterprise] 3.5 SATA; drive support for rack units on the front; 32 GB DDR4 SDRAM (2x 16 GB), dual channel, TPM 2.0; PCS 7 V10.0 SP1 preinstalled; Windows Server IoT 2022 Standard Edition including 16 cores, 5 clients, 64-bit, MUI (en, de, fr, it, es, zh), 64-bit, with restore USB flash drive; enclosure blue chromated, Industrial Ethernet (CP1623), (1 slot occupied); 100/240 V AC industrial power supply unit, power supply cord Europe;

Approvals / Certificates

General Product Approval



EG-Konf.



[Manufacturer Declaration](#)



CB



UL



RCM

General Product Approval

Environment



[BIS CRS](#)

[KC](#)

[Environmental Confirmations](#)



last modified:

11/26/2025