



E3ZM-B81 2M

Photoelectric sensor, rectangular housing, stainless steel, red LED, retro-reflective, transparent object, 500 mm, with teach-button, PNP, Light-ON/Dark-ON, 2 m cable

Specifications

Shape	Cuboid
Sensing method	Retro-reflective
Sensing distance	500 mm
Sensing distance (min.)	100 mm
Setting method	Teach-In
Connection method	Cable
Cable length	2 m
Output type	PNP
Operation mode	Dark-ON, Light-ON
Response time	1 ms
Material housing	Stainless steel
Thread size	Other
Product Width (unpacked)	10.8 mm
Product Height (unpacked)	31 mm
Product Depth (unpacked)	21 mm
Type of light	Polarized red light
Power supply voltage	10-30 V
Features	M.S.R., Transparent detection (PET bottle and tray)
Degree of protection (IP)	IP67/IP69K

Accessories



E39-L104

Mounting bracket for E3Z sensor, standard, vertical mounting



E39-L142

Mounting Bracket, protective side wall (for E3Z)



E39-L144

Sensor mounting Bracket, Protective bracket for E3Z pre-wired



E39-L150

Sensor mounting Bracket for E3Z, 100mm high post



E39-L151

Sensor mounting Bracket, for E3Z, 200mm high post



E39-L153

Mounting bracket for E3Z sensor, L shape, for prewired



E39-L43

Mounting bracket for E3Z sensor, side mounting



E39-L44

Mounting bracket for E3Z sensor, rear mounting



E39-L98

Protective metal cover for E3S-A/E3Z vertical sensor



E39-RP1

Reflector, polarizing, to use with E3ZM-B, 44mm x 64mm

CAD Library



E3Z **Brochure**

EN PDF 1.34 MB



E3ZM-B Series **Datasheet**

EN PDF 2.86 MB



EAC Mark removal **Discontinuation Notice**

EN PDF 221 KB