



MYQ4N 220/240VAC

Plastic sealed relay, plug-in, 14-pin, 4PDT, 1 A, with LED, 220/240 VAC

Specifications

Mounting method	With plug-in socket
Usage	General purpose
Poles	4
Rated carry current	1 A
Coil voltage	240 V
Operation voltage	AC
Contact material	Ag alloy + Au plating
Contact description	4PDT
Features	Au plating, LED, Plastic sealed, Transparent case
Terminal type	Plug-in



PYF-14-PU

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals



PYF-14-PU-L

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals,



PYF14-ESN-B

Socket, with common and coil terminals on the bottom and with the NC & NO terminal on the top - Black.



PYF14-ESS-B

Socket, with coil terminals on the bottom and with the common and NC & NO terminals on the top - Black.



PYF14S

Socket, DIN rail mounting, 14-pin, screwless terminals



PYFZ-14-E

Socket, DIN rail/surface mounting, 14-pin, screw terminals (standard)

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



Industrial Relays Brochure

EN PDF 2.77 MB



MY(S) Miniature Power Relays Datasheet

EN PDF 9.24 MB



OMRON Manufacturing Know-How: High Quality Relays Leaflet

EN PDF 449 KB



Solution case study No.8 Environment resistance Brochure

EN PDF 623 KB