



PYF-14-PU

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals

Specifications

Applicable product family	H3YN, MY2K, MY4, MY4-GS
Mounting method	DIN rail/screw
Terminal type	Push-in Plus
Product Width (unpacked)	31 mm
Product Height (unpacked)	90 mm
Product Depth (unpacked)	67.5 mm
Color	Black
Hold down clip included	✓
Release Lever included	✓
Applicable wire	Solid, Stranded, With ferrules
Applicable ferrules	Round terminals

Fits to



MY4-GS-R AC110/120

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 100/110 VAC



MY4-GS-R AC12

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 12 VAC



MY4-GS-R AC220/240

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 220/240 VAC



MY4-GS-R AC24

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 24 VAC

**MY4-GS-R AC48**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 48 VAC

**MY4-GS-R DC100/110**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 100/110 VDC

**MY4-GS-R DC12**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 12 VDC

**MY4-GS-R DC24**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 24 VDC

**MY4-GS-R DC48**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 48 VDC

**MY4H 110/120VAC**

Relay, plug-in, 14-pin, 4PDT, 3 A, hermetically-sealed

**MY4H 12VDC**

Relay, plug-in, 14-pin, 4PDT, 3 A, hermetically-sealed

**MY4H 24VAC**

Hermetically-sealed relay, plug-in, 14-pin, 4PDT, 3 A, 24 VAC

**MY4H 24VDC**

Relay, plug-in, 14-pin, 4PDT, 1 A, hermetically-sealed

**MY4IN-CR-GS-R AC110/120**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button. 110/120 VAC

**MY4IN-CR-GS-R AC220/240**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button. 220/240 VAC

**MY4IN-D2-GS-R DC12**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button, 12 VDC

**MY4IN-D2-GS-R DC24**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button, 24 VDC

**MY4IN-GS-R AC110/120**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 110/120 VAC

**MY4IN-GS-R AC12**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 12 VAC

**MY4IN-GS-R AC200/220**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 200/220 VAC



MY4IN-GS-R AC220/240

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical &
LED indicators, lockable
push test button, 220/240
VAC.



MY4IN-GS-R AC24

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical &
LED indicators, lockable
push test button, 24 VAC



MY4IN-GS-R AC48

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical &
LED indicators, lockable
push test button, 48 VAC



MY4IN-GS-R DC100/110

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical &
LED indicators, lockable
push test button, 100/110
VDC.



MY4IN-GS-R DC12

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical &
LED indicators, lockable
push test button, 12 VDC



MY4IN-GS-R DC24

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical &
LED indicators, lockable
push test button, 24 VDC



MY4IN-GS-R DC48

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical &
LED indicators, lockable
push test button, 48 VDC



MY4N-GS-R DC24

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical &
LED indicators, 24 VDC



MY4Z 110/120VAC (S)

Relay, plug-in, 14-pin,
bifurcated contacts, 4PDT, 5
A, mech indicator, label
facility, 100/120 VAC



MY4Z 220/240VAC (S)

Relay, plug-in, 14-pin,
bifurcated contacts, 4PDT, 5
A, mech indicator, label
facility, 220/240 VAC



MY4Z 24VDC (S)

Relay, plug-in, 14-pin,
bifurcated contacts, 4PDT, 5
A, mech indicator, label
facility, 24 VDC



MY4ZH 100/110VAC

Hermetically-sealed relay,
plug-in, 14-pin, 4PDT, 3 A,
bifurcated contacts, 110
VAC



MY4ZH 24VDC

Hermetically-sealed relay,
plug-in, 14-pin, 4PDT, 3 A,
bifurcated contacts



MY4ZIN 220/240VAC (S)

Relay, plug-in, 4PDT
(bifurcated), 3 A, mech. +
LED indicator, test button,
220/240 VDC



MY4ZIN 24VAC (S)

Relay, plug-in, 4PDT
(bifurcated), 3 A, mech. +
LED indicator, test button,
24 VAC



MY4ZIN 24VDC (S)

Relay, plug-in, 4PDT
(bifurcated), 3 A, mech. +
LED indicator, test button,
24 VDC

**MY4ZIN-D2 24VDC (S)**

Relay, plug-in, 14-pin, 4PDT, bifurcated contacts, 5 A, mech & LED indicators, coil suppressor, lockable push to test button, label facility, 24 VDC

**MY4ZIN1 24VDC (S)**

Relay, plug-in, 4PDT (bifurcated), reverse coil polarity, 3 A, mech. + LED indicator, test button, 24 VDC

**MY4ZN 110/120VAC (S)**

Relay, plug-in, 14-pin, 4PDT, bifurcated contacts, 5 A, mech & LED indicators, label facility, 110/120 VAC

**MY4ZN 220/240VAC (S)**

Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, 220/240 VAC

**MY4ZN 24VAC (S)**

Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, 24 VAC

**MY4ZN 24VDC (S)**

Relay, plug-in, 14-pin, 4PDT, bifurcated contacts, 5 A, mech & LED indicators, label facility, 24 VDC

**MY4ZN 48/50VAC (S)**

Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, 48/50 VAC

**MY4ZN-CR 110/120VAC (S)**

Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, RC circuit, 110/120 VAC

**MY4ZN-CR 220/240VAC (S)**

Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, RC circuit, 220/240 VAC

**MY4ZN-D2 100/110VDC (S)**

Relay, plug-in, 14-pin, 4PDT, bifurcated contacts, 5 A, mech & LED indicators, coil suppressor label facility, 100/110 VDC

**MY4ZN-D2 24VDC (S)**

Relay, plug-in, 14-pin, 4PDT, bifurcated contacts, 5 A, mech & LED indicators, coil suppressor label facility, 24 VDC

**MY4ZN-D2 48VDC (S)**

Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, diode, 48 VDC

**MY4ZN1-D2 24VDC (S)**

Relay, plug-in, 4PDT (bifurcated), reverse coil polarity, 3 A, mech. + LED indicator, diode, 24 VDC

**MYQ4 110/120VAC**

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, 110/120 VAC

**MYQ4 220/240VAC**

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, 220/240 VAC

**MYQ4 24VDC**

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, 24 VDC

**MYQ4N 110/120VAC**

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, with indicator, 110/120 VAC

**MYQ4N 220/240VAC**

Plastic sealed relay, plug-in, 14-pin, 4PDT, 1 A, with LED, 220/240 VAC

**MYQ4N 24VAC**

Plastic sealed relay, plug-in, 14-pin, 4PDT, 1 A, with LED, 24 VAC

**MYQ4N 24VDC**

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, with indicator, 24 VDC

**MYQ4Z 200/220VAC**

Plastic sealed relay, plug-in, 14-pin, 4PDT, 1 A, bifurcated contacts

Accessories

**PFP-100N**

DIN-rail mounting track, 35 x 7.3 mm, 1 m length

**PFP-100N2**

DIN-rail mounting track, 35x16mm, 1m length

**PFP-50N**

Din rail track, 500 mm

**PFP-M**

End plate

**PFP-S**

Spacer



PYDN-15.5-080R

Accessory for PYF-PU, 15.5mm pitch, 8 Poles, Red color



PYDN-31.0-080S

Accessory for PYF-PU, 31mm pitch, 8 Poles, Blue color



PYDN-31.0-080Y

Accessory for PYF-PU, 31mm pitch, 8 Poles, Yellow color



PYDN-7.75-020R

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 2 Poles, Red color



PYDN-7.75-020S

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 2 Poles, Blue color



PYDN-7.75-020Y

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 2 Poles, Yellow color




PYDN-7.75-030R

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 3 Poles, Red color



PYDN-7.75-030S

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 3 Poles, Blue color



PYDN-7.75-030Y

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 3 Poles, Yellow color




PYDN-7.75-040R

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 4 Poles, Red color



PYDN-7.75-040S

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 4 Poles, Blue color



PYDN-7.75-040Y

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 4 Poles, Yellow color



PYDN-7.75-200R

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 20 Poles, Red color



PYDN-7.75-200S

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 20 Poles, Blue color



PYDN-7.75-200Y

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 20 Poles, Yellow color



XW5Z-EP12

Separator Plate for terminal blocks, 12 mm width



XW5Z-EP6

End bracket for terminal blocks, 6 mm width



Y92F-78

Flush panel mounting adapter for H3Y(N) timer



Y92H-3

Clips for H3Y(N) timer & PYF socket

Downloads

CAD Library



**EAC Mark removal
Discontinuation Notice**

EN PDF 221 KB



**PYF-__-PU/PTF-__-
PU/P2RF-__-PU Sockets
with Push-In Plus
technology**

Datasheet

EN PDF 2.59 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 27 November, 2025. [Click here for terms of use.](#)

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU