



Connection terminal Central cable entry 690 V AC, 1000 V DC, 125 A IP20

Model	
product brand name	SETRON
product designation	Busbar systems
design of the product	Accessories
Supply voltage	
operating voltage at AC rated value	690 V
Connections	
tightening torque	
• minimum	1 N·m
• maximum	3.5 N·m
type of connectable conductor cross-sections for copper conductor stranded	6-50 mm ²
Mechanical Design	
height	27 mm
width	16.5 mm
depth	20 mm
length	33.5 mm
Net Weight	23 g
Approvals Certificates	
General Product Approval	other



[Miscellaneous](#)



[Confirmation](#)



Environment

[Environmental Confirmations](#)

[Environmental Confirmations](#)

Further information

- Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
- Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/lowvoltage/catalogs>
- Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3760-3>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3760-3>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3760-3

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

last modified:

4/11/2025 

