



circuit breaker VL150 UL type DG (cat no. NDK3B125) non-interchangeable frame, with circuit breaker approval acc. to UL 489 standard breaking capacity 3-pole; NEMA rating 35KA@480V and 18KA@600/347V (molded case circuit breaker) Electronic Trip Unit TM, LI TA=40°C In=125A, rated current II=625...1250A short-circuit protection Ir=125A Electronic Trip Unit for line protection without connection accessories without auxiliary release without auxiliary/alarm switch, spare part product only for replacement purposes

Weight	2.175 kg
Net Weight	2.175 kg

### Approvals / Certificates

General Product Approval	other
--------------------------	-------



[Confirmation](#)

other	Environment
-------	-------------

[Miscellaneous](#)

[Miscellaneous](#)

[Environmental Con-  
firmations](#)

[Environmental Con-  
firmations](#)

### Further information

#### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

#### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

#### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL2512-1KN30-0AA0>

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VL2512-1KN30-0AA0>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VL2512-1KN30-0AA0](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL2512-1KN30-0AA0)

#### CAX-Online-Generator

<https://www.siemens.com/cax>

#### Information- and Downloadcenter (catalogues, leaflets,...)

<https://www.siemens.com/energy-automation>



last modified:

4/8/2025

