

Product datasheet

Specifications

W650 ADJUSTABLE MOD. DEV. RAIL PRISMA P



LVS03402

EAN Code: 3606481875570

Main

Range	PrismaSeT
Range of product	PrismaSeT P
Product or component type	Rail
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT P
Type of rail	Adjustable Modular
Installed device	TeSys: fixed GV2L TeSys: fixed GV2P TeSys: fixed GV3 ComPact: fixed NG160 without earth leakage protection - control: toggle ComPact: fixed NG160 NA without earth leakage protection - control: toggle ComPact: fixed NG160 with earth leakage protection - control: toggle Altistart: ATS01N Altistart: ATS01N103/106FT TeSys: fixed D or K contactors <= 40 A - horizontal installation TeSys: fixed GV2 + D or K contactors <= 40 A - horizontal installation TeSys: fixed TeSys U - horizontal installation PowerLogic: PM5500 PowerLogic: iEM3000 PowerLogic: PM3000 PowerLogic: PM5563RD ComPact: fixed NSXm without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSXm with earth leakage protection - control: toggle - vertical installation

Poles description	9 x 3P: fixed GV2L 9 x 3P: fixed GV2P 7 x 3P: fixed GV3 1 x 3P: fixed NG160 1 x 4P: fixed NG160 1 x 3P: fixed NG160 NA 1 x 4P: fixed NG160 NA 9 x 4P: fixed D or K contactors <= 40 A horizontal installation 9 x 3P: fixed GV2 + D or K contactors <= 40 A horizontal installation 9 x 3P: fixed TeSys U horizontal installation 1 x 3P or 4P: fixed NSXm vertical installation
-------------------	--

Complementary

installation description	Cubicle - width 650 mm depth 400 mm
Enclosure nominal height	2000 mm

Number of vertical modules [50 mm]	5 module(s): ATS01N in 650 mm Widecubicle 6 module(s): ATS01N in 650 mm Widecubicle 4 module(s): ATS01N103/106FT in 650 mm Widecubicle 3 module(s): D or K contactors <= 40 A, direct in 650 mm Widecubicle 5 module(s): GV2 + D or K contactors <= 40 A, direct in 650 mm Widecubicle 3 module(s): GV2L, direct in 650 mm Widecubicle 3 module(s): GV2P, direct in 650 mm Widecubicle 5 module(s): GV3, direct in 650 mm Widecubicle 4 module(s): iEM3000 in 650 mm Widecubicle 5 module(s): NG160 without earth leakage protection , direct in 650 mm Widecubicle 5 module(s): NG160 NA without earth leakage protection , direct in 650 mm Widecubicle 8 module(s): NSXm without earth leakage protection , direct in 650 mm Widecubicle 4 module(s): PM3000 in 650 mm Widecubicle 3 module(s): PM5500 in 650 mm Widecubicle 3 module(s): PM5563RD in 650 mm Widecubicle 5 module(s): TeSys U, direct in 650 mm Widecubicle 4 module(s): TeSys U, direct in 650 mm Widecubicle 5 module(s): NG160 with earth leakage protection , direct in 650 mm Widecubicle 8 module(s): NSXm with earth leakage protection , direct in 650 mm Widecubicle
9 mm pitches	48
Quantity per set	Set of 1
Height	30 mm
Width	563 mm
Depth	325 mm
Net weight	0.86 kg
Colour	Natural
Material	Metal

Environment

Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASTA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.000 cm
Package 1 Width	4.500 cm
Package 1 Length	52.000 cm
Package 1 Weight	806.000 g
Unit Type of Package 2	S04
Number of Units in Package 2	20
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	16.970 kg
Unit Type of Package 3	P12
Number of Units in Package 3	160
Package 3 Height	73.000 cm
Package 3 Width	80.000 cm

Package 3 Length	120.000 cm
------------------	------------

Package 3 Weight	142.960 kg
------------------	------------

Logistical informations

Country of origin	FR
-------------------	----

Contractual warranty

Warranty (in months)	18
----------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant

REACH Regulation

[REACH Declaration](#)

Halogen-free status

Halogen free plastic parts product

PVC free

Yes

Silicone-free

Yes

Use Again

Repack and remanufacture

End of life manual availability

No need of specific recycling operations

Take-back

No