


Product datasheet

Specifications



TAP OFF UNIT 630A FUSE

KSB630SE4

EAN Code: 3606480005657

Main

Range of product	Canalis
Range compatibility	Canalis KS busbar trunking
Product or component type	Tap-off unit
busbar trunking compatibility	Canalis KS busbar trunkingplug-in
[Ie] rated operational current	630 A at 35 °C
protection type	fuse isolator: blade type fuse, size 3 conforming to NF or DIN
Provided equipment	fuse to be ordered separately
Mounting mode	Plug-in with fixed polarity
Tap-off unit polarity	3L+N+PE
Colour	White (RAL 9001)

Complementary

Device application	Medium power distribution
[Uimp] rated impulse withstand voltage	6.8 kV
[Ui] rated insulation voltage	500 V depending on protective device
Network frequency	50/60 Hz
Electrical connection	Copper cable lug - ISO40 480 mm ² flexible Copper cable lug - ISO40 480 mm ² rigid
door/cover opening side	Right
Tap-off unit disconnection mode	By opening the door
Standards	IEC 61439-1 IEC 61439-6
Body material	Metal
Width	1144.5 mm
Depth	300 mm
depth (door open)	1106.5 mm
Height	611 mm
Net weight	59 kg

Environment

Earthing system	TT TN-S IT
-----------------	------------------

IP degree of protection	IP55 conforming to IEC 60529
--------------------------------	------------------------------

IK degree of protection	IK08 conforming to IEC 62262
--------------------------------	------------------------------

Packing Units

Unit Type of Package 1	PCE
-------------------------------	-----

Number of Units in Package 1	1
-------------------------------------	---

Package 1 Height	37.1 cm
-------------------------	---------

Package 1 Width	63 cm
------------------------	-------

Package 1 Length	110.5 cm
-------------------------	----------

Package 1 Weight	61.06 kg
-------------------------	----------

Contractual warranty

Warranty (in months)	18
-----------------------------	----




Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.



[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	Fbe82b7c-542c-4391-913a-58c8f489ca40
REACH Regulation	REACH Declaration
Halogen-free status	Halogen free product
PVC free	Yes
Silicone-free	Yes

Use Again

 Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins