

Product datasheet

Specifications



TAP OFF UNIT 400A FUSE T2

Local distributor code:

389359951

KSB400SE4

EAN Code: 3606480005817

Main

Range of product	Canalis
Range compatibility	Canalis KT busbar trunking Canalis KS busbar trunking
Product or component type	Tap-off unit
busbar trunking compatibility	Canalis KS busbar trunking plug-in Canalis KT busbar trunking with KS type plug-in
[Ie] rated operational current	400 A at 35 °C
protection type	fuse isolator: for aM blade type fuse, size 2 - 400 A conforming to NF fuse isolator: for gG blade type fuse, size 2 - 400 A conforming to NF
Provided equipment	fuse to be ordered separately
Mounting mode	Plug-in with fixed polarity
Tap-off unit polarity	3L+N+PE
Colour	White (RAL 9001)

Complementary

Device application	Medium power distribution
[Ue] rated operational voltage	230...690 V depending on protective device
[Uimp] rated impulse withstand voltage	6.8 kV
[Ui] rated insulation voltage	500 V depending on protective device
Network frequency	50/60 Hz
Electrical connection	Copper cable lug - ISO50 240 mm ² flexible Copper cable lug - ISO50 240 mm ² rigid
door/cover opening side	Right
Tap-off unit disconnection mode	By opening the door
Standards	IEC 61439-1 IEC 61439-6
Body material	Metal
Width	600 mm
Depth	316 mm
depth (door open)	855 mm
Height	600 mm
Net weight	29.2 kg

Environment

Earthing system	TT TN-S IT
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	39.0 cm
Package 1 Width	65.0 cm
Package 1 Length	66.0 cm
Package 1 Weight	30.3 kg
Unit Type of Package 2	P12
Number of Units in Package 2	3
Package 2 Height	80.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	102.9 kg

Contractual warranty

Warranty (in months)	18
-----------------------------	----




Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.



[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	Fbe82b7c-542c-4391-913a-58c8f489ca40
REACH Regulation	REACH Declaration
Halogen-free status	Halogen free product
PVC free	Yes
Silicone-free	Yes

Use Again

 Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins