



PRODUCT-DETAILS

# XLP1

## XLP1 Fuse Switch Disconnecter




---

General Information	
Extended Product Type	XLP1
Product ID	1SEP101891R0001
EAN	7025840013723
Catalog Description	XLP1 Fuse Switch Disconnecter
Long Description	XLP1,3-pole,250A, without clamps or bolts

---

ABB EcoSolutions	
ABB EcoSolutions	Yes
ABB Site Meeting Group Waste To Landfill Target	No non-hazardous waste is sent to a landfill UL 2799 Zero Waste To Landfill Validation available
End Of Life Disassembling Instructions	9AKK108469A3432
Environmental Product Declaration - EPD	9AKK108468A2201 9AKK108468A2281
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 94.1 %

---

### Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201
RoHS Declaration	1SCC011020D0201
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

## Popular Downloads

Data Sheet, Technical Information	1SEC312012D0201
Instructions and Manuals	No Instructions and Manuals needed
Environmental Product Declaration - EPD	9AKK108468A2201 9AKK108468A2281

## Environmental

Degree of Protection	IP30
----------------------	------

## Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85389099
Country or Territory of Origin	Bulgaria China

## Dimensions

Product Net Width	185 mm
Product Net Height	270 mm
Product Net Depth / Length	116 mm
Product Net Weight	1.6 kg

## Container Information

Package Level 1 Units	shrink-wrap 1 piece
Package Level 1 Width	185 mm
Package Level 1 Depth / Length	116 mm
Package Level 1 Height	270 mm
Package Level 1 Gross Weight	1.6 kg
Package Level 1 EAN	7025840013723
Package Level 2 EAN	7025840013723

## Technical

Degree of Protection	IP30
Device Type Manager (DTM)	Fuseswitchdisconnector
Electronic Fuse Monitoring	No
Fuse Size	NH1
Fuse System	DIN
Handle Type	Front cover 3P
Mounting Type	Baseplate

Number of Poles	3P
Power Loss	at Rated Load 7.5 W
Rated Conditional Short-Circuit Current ( $I_{nc}$ )	(690 V) 50 kiloampere rms
Rated Current ( $I_n$ )	250 A
Rated Frequency (f)	Main Circuit 50/60 Hz
Rated Impulse Withstand Voltage ( $U_{imp}$ )	Main Circuit 8 kV
Rated Operational Current AC-21B ( $I_e$ )	(690 V) 200 A
Rated Operational Current AC-22B ( $I_e$ )	(500 V) 250 A (800 V) 250 A
Rated Operational Voltage	500 V AC 690 V AC 800 V AC
Rated Voltage ( $U_r$ )	500 V AC 690 V AC 800 V AC
Special Functions	Not Included
Standards	IEC60947-3 GB/T14048.3
Terminal Type	Lug terminals

## Certificates and Declarations

Declaration of Conformity - CE	1SEP500050P0001
--------------------------------	-----------------

## External Classifications and Standards

Object Classification Code	S
ETIM 9	EC001040 - Fuse switch disconnecter
ETIM 10	EC001040 - Fuse switch disconnecter
UNSPSC	39121600
eClass	V11.1 : 27371401
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3601050
E-Number (Sweden)	2307320

## Categories

Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → EasyLine

