



## G3PW-A220EC-C-FLK

Single phase power controller, constant current type, 20 A, SLC terminals

# Specifications

Application	Power control
Number of phases	1
Mounting method	Screw
Terminal type	Push-in, Screw
Features	Constant current
LED indicator	✓
Rated operational voltage, AC	100-240 V
Operating voltage range, AC	85-264 V
Rated operation current I <sub>e</sub> at AC-1	20 A
Permissible I <sup>2</sup> t value	400 A <sup>2</sup> s
Applicable heater capacity (AC1: resistive load)	5 kW
Product Height (unpacked)	170 mm
Product Width (unpacked)	50 mm
Product Depth (unpacked)	137 mm
Supply voltage DC	1-5 V
Maximum operating temperature	55 °C
Minimum operating temperature	-15 °C
Switching at zero-crossing	✗
Functions	Heater burnout detection
Communication port(s)	Serial RS-485



**G32X-V2K**

External variable resistor, 2 kW, for G3PW power controller

## Downloads

CAD Library



**EAC Mark removal  
Discontinuation Notice**

EN PDF 221 KB



**G3PW Power  
Controllers  
Users Manual**

EN PDF 2.1 MB



**G3PW Single-phase  
Power Controller  
Datasheet**

EN PDF 2.49 MB