

# Product datasheet

Specifications



## TeSys D reversing contactor - 3P(3 NO) - AC-3 - <= 440 V 9 A - 24 V DC coil

Local distributor code:

389755885

LC2D093BL

⚠ Discontinued on: 9 Feb 2023

⚠ Discontinued

EAN Code: 3389110716450

## Main

|   |  |
|---|--|
| Range                                       | TeSys<br>TeSys Deca  |
| Product name                                | TeSys D<br>TeSys Deca  |
| Product or component type                   | Reversing contactor  |
| Device short name                           | LC2D   |
| Contactor application                       | Resistive load<br>Motor control  |
| Utilisation category                        | AC-1<br>AC-3<br>AC-3e  |
| Device presentation                         | Preassembled with reversing power busbar   |
| Poles description                           | 3P   |
| power pole contact composition              | 3 NO   |
| [Ue] rated operational voltage              | Power circuit: <= 690 V AC 25...400 Hz<br>Power circuit: <= 300 V DC   |
| [Ie] rated operational current              | 9 A (at <60 °C) at <= 440 V AC AC-3 for power circuit<br>16 A (at <60 °C) at <= 440 V AC AC-1 for power circuit  |
| Motor power kW                              | 2.2 kW at 220...230 V AC 50...60 Hz<br>4 kW at 380...400 V AC 50...60 Hz<br>4 kW at 415 V AC 50...60 Hz<br>4 kW at 440 V AC 50...60 Hz<br>5.5 kW at 500 V AC 50...60 Hz<br>5.5 kW at 660...690 V AC 50...60 Hz   |
| Motor power hp                              | 0.5 hp at 115 V AC 60 Hz for 1 phase motors<br>1 hp at 230/240 V AC 60 Hz for 1 phase motors<br>2 hp at 200/208 V AC 60 Hz for 3 phases motors<br>2 hp at 230/240 V AC 60 Hz for 3 phases motors<br>5 hp at 460/480 V AC 60 Hz for 3 phases motors<br>7.5 hp at 575/600 V AC 60 Hz for 3 phases motors |
| Control circuit type                        | DC low consumption   |
| [Uc] control circuit voltage                | 24 V DC  |
| Auxiliary contact composition               | 1 NO + 1 NC  |
| [Uimp] rated impulse withstand voltage      | 6 kV conforming to IEC 60947   |
| Overvoltage category                        | III  |
| [Ith] conventional free air thermal current | 16 A (at 60 °C) for power circuit<br>10 A (at 60 °C) for signalling circuit  |

|   |  |
|---|--|
| <b>Irms rated making capacity</b>               | 250 A at 440 V for power circuit conforming to IEC 60947<br>140 A AC for signalling circuit conforming to IEC 60947-5-1<br>250 A DC for signalling circuit conforming to IEC 60947-5-1   |
| <b>Rated breaking capacity</b>                  | 250 A at 440 V for power circuit conforming to IEC 60947   |
| <b>[Icw] rated short-time withstand current</b> | 30 A 40 °C - 10 min for power circuit<br>61 A 40 °C - 1 min for power circuit<br>105 A 40 °C - 10 s for power circuit<br>210 A 40 °C - 1 s for power circuit<br>100 A - 1 s for signalling circuit<br>120 A - 500 ms for signalling circuit<br>140 A - 100 ms for signalling circuit   |
| <b>Associated fuse rating</b>                   | 25 A gG at <= 690 V coordination type 1 for power circuit<br>20 A gG at <= 690 V coordination type 2 for power circuit<br>10 A gG for signalling circuit conforming to IEC 60947-5-1   |
| <b>Average impedance</b>                        | 2.5 mOhm - Ith 16 A 50 Hz for power circuit  |
| <b>[Ui] rated insulation voltage</b>            | Power circuit: 690 V conforming to IEC 60947-4-1<br>Power circuit: 600 V CSA certified<br>Power circuit: 600 V UL certified<br>Signalling circuit: 690 V conforming to IEC 60947-1<br>Signalling circuit: 600 V CSA certified<br>Signalling circuit: 600 V UL certified  |
| <b>Electrical durability</b>                    | 0.6 Mcycles 25 A AC-1 at Ue <= 440 V<br>2 Mcycles 9 A AC-3 at Ue <= 440 V<br>2 Mcycles 9 A AC-3e at Ue <= 440 V  |
| <b>Power dissipation per pole</b>               | 0.2 W AC-3<br>1.56 W AC-1<br>0.2 W AC-3e   |
| <b>Front cover</b>                              | With   |
| <b>Interlocking type</b>                        | Mechanical   |
| <b>Mounting support</b>                         | Plate<br>Rail  |
| <b>Standards</b>                                | CSA C22.2 No 14<br>EN 60947-4-1<br>EN 60947-5-1<br>IEC 60947-4-1<br>IEC 60947-5-1<br>UL 60335-2-40:Annex JJ<br>IEC 60335-1   |
| <b>Product certifications</b>                   | DNV<br>CSA<br>CCC<br>UL<br>GL<br>LROS (Lloyds register of shipping)<br>BV<br>RINA<br>GOST<br>UKCA  |
| <b>Connections - terminals</b>                  | Power circuit: spring terminals 1 cable(s) 2.5 mm <sup>2</sup> flexible without cable end<br>Power circuit: spring terminals 2 cable(s) 2.5 mm <sup>2</sup> flexible without cable end<br>Control circuit: spring terminals 1 cable(s) 2.5 mm <sup>2</sup> flexible without cable end<br>Control circuit: spring terminals 2 cable(s) 2.5 mm <sup>2</sup> flexible without cable end |
| <b>Tightening torque</b>                        | Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2<br>Power circuit: 2.5 N.m - on screw clamp terminals - with screwdriver pozidriv No 2   |
| <b>Operating time</b>                           | 65.45...88.55 ms closing<br>20...30 ms opening   |
| <b>Safety reliability level</b>                 | B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1   |
| <b>Mechanical durability</b>                    | 30 Mcycles   |
| <b>Maximum operating rate</b>                   | 3600 cyc/h 60 °C   |

## Complementary

|                                       |   |
|---------------------------------------|---|
| <b>Coil technology</b>                | Built-in bidirectional peak limiting diode suppressor   |
| <b>Control circuit voltage limits</b> | 0.1...0.3 U <sub>c</sub> (-40...70 °C):drop-out DC<br>0.8...1.25 U <sub>c</sub> (-40...60 °C):operational DC<br>1...1.25 U <sub>c</sub> (60...70 °C):operational DC |
| <b>Time constant</b>                  | 40 ms   |
| <b>Inrush power in W</b>              | 2.4 W (at 20 °C)  |
| <b>Hold-in power consumption in W</b> | 2.4 W at 20 °C  |
| <b>Auxiliary contacts type</b>        | type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1<br>type mirror contact 1 NC conforming to IEC 60947-4-1  |
| <b>Signalling circuit frequency</b>   | 25...400 Hz   |
| <b>Minimum switching current</b>      | 5 mA for signalling circuit   |
| <b>Minimum switching voltage</b>      | 17 V for signalling circuit   |
| <b>Non-overlap time</b>               | 1.5 ms on de-energisation between NC and NO contact<br>1.5 ms on energisation between NC and NO contact   |
| <b>Insulation resistance</b>          | > 10 MOhm for signalling circuit  |

## Environment

|  |  |
|--|--|
| <b>IP degree of protection</b>               | IP20 front face conforming to IEC 60529  |
| <b>Climatic withstand</b>                    | conforming to IACS E10<br>conforming to IEC 60947-1 Annex Q category D   |
| <b>Protective treatment</b>                  | TH conforming to IEC 60068-2-30  |
| <b>Pollution degree</b>                      | 3  |
| <b>Ambient air temperature for operation</b> | -40...60 °C<br>60...70 °C with derating  |
| <b>Ambient air temperature for storage</b>   | -60...80 °C  |
| <b>Operating altitude</b>                    | 0...3000 m   |
| <b>Fire resistance</b>                       | 850 °C conforming to IEC 60695-2-1   |
| <b>Flame retardance</b>                      | V1 conforming to UL 94   |
| <b>Mechanical robustness</b>                 | Vibrations contactor open: 2 Gn, 5...300 Hz<br>Vibrations contactor closed: 4 Gn, 5...300 Hz<br>Shocks contactor open: 10 Gn for 11 ms<br>Shocks contactor closed: 15 Gn for 11 ms |
| <b>Height</b>                                | 99 mm  |
| <b>Width</b>                                 | 90 mm  |
| <b>Depth</b>                                 | 95 mm  |
| <b>Net weight</b>                            | 1.017 kg   |

## Packing Units

|                                     |          |
|-------------------------------------|----------|
| <b>Unit Type of Package 1</b>       | PCE      |
| <b>Number of Units in Package 1</b> | 1        |
| <b>Package 1 Height</b>             | 13.5 cm  |
| <b>Package 1 Width</b>              | 11.4 cm  |
| <b>Package 1 Length</b>             | 11 cm    |
| <b>Package 1 Weight</b>             | 1.224 kg |

---

|                                     |          |
|-------------------------------------|----------|
| <b>Unit Type of Package 2</b>       | S02      |
| <b>Number of Units in Package 2</b> | 5        |
| <b>Package 2 Height</b>             | 15 cm    |
| <b>Package 2 Width</b>              | 30 cm    |
| <b>Package 2 Length</b>             | 40 cm    |
| <b>Package 2 Weight</b>             | 6.458 kg |

---

## Logistical informations

---

Country of origin FR

## Contractual warranty

---

Warranty (in months) 18



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint 39

Environmental Disclosure [Product Environmental Profile](#)

### Use Better

#### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic Yes

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 50ae7612-fd2e-41e4-a369-50d0dea6e592

REACH Regulation [REACH Declaration](#)

PVC free Yes

### Use Again

#### Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins