

Product datasheet

Specifications



DIN socket iPC - 2P+E - 16A - 250VAC - NFC 15100 - french std

A9A15306

EAN Code: 3606480097768

Main

range of product	Acti9
Product name	Acti9 iPC
Product or component type	Modular socket-outlet
Device short name	iPC
Poles description	2P + E
Outlet standard	French

Complementary

[In] rated current	16 A
[Ue] rated operational voltage	250 V AC 50/60 Hz
Mounting mode	Fixed
Mounting support	Symmetrical DIN rail
9 mm pitches	5
Height	84 mm
Width	45 mm
Depth	60 mm
Net weight	98 g
Colour	White
Connections - terminals	Tunnel type terminal1 cable(s) 6 mm ² flexible Tunnel type terminal1 cable(s) 10 mm ² rigid
Wire stripping length	13 mm
Tightening torque	1.2 N.m

Environment

Standards	IEC 60884-1 NF C 15-100 NF C 61-314
IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
IK degree of protection	IK03
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...70 °C

Ambient air temperature for storage	-40...80 °C
-------------------------------------	-------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	6.500 cm
------------------	----------

Package 1 Width	4.500 cm
-----------------	----------

Package 1 Length	8.500 cm
------------------	----------

Package 1 Weight	102.000 g
------------------	-----------

Unit Type of Package 2	BB1
------------------------	-----

Number of Units in Package 2	5
------------------------------	---

Package 2 Height	2.750 cm
------------------	----------

Package 2 Width	30.000 cm
-----------------	-----------

Package 2 Length	20.000 cm
------------------	-----------

Package 2 Weight	560.000 g
------------------	-----------

Unit Type of Package 3	S03
------------------------	-----

Number of Units in Package 3	75
------------------------------	----

Package 3 Height	30.000 cm
------------------	-----------

Package 3 Width	30.000 cm
-----------------	-----------

Package 3 Length	40.000 cm
------------------	-----------

Package 3 Weight	8.878 kg
------------------	----------

Logistical informations

Country of origin	BE
-------------------	----

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 26

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic Yes

[EU RoHS Directive](#) Compliant

SCIP Number 298247e9-8385-4c4a-aeaf-df8136a7fb49

REACH Regulation [REACH Declaration](#)

Halogen-free status Product contains halogen above thresholds

Use Again

Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins