

**080G0115****Program. controller, 6 relays, MCX06D**

Function: Programmable Controller, Supply voltage [V] AC: 24, Communication type: CANBUS; RS485; MODBUS, Packing format: Single pack, Quantity per packing format: 1

**PRODUCT DETAILS**

<b>Gross weight</b>	0.326 Kilogram
<b>Net weight</b>	0.227 Kilogram
<b>Volume</b>	1.956 Liter
<b>EAN</b>	5702423285341
<b>Type</b>	MCX06D
<b>Product group</b>	Programmable controllers
<b>Product Name Description</b>	Program. controller, 6 relays
<b>1 Primary battery SUM weight Kg</b>	0.001
<b>1 Primary battery weight Kg</b>	0.001
<b>Analog inputs (AI) [pc]</b>	4 pc
<b>Analog outputs (AO) [pc]</b>	3 pc
<b>Approval</b>	CE CMIM EAC GOST R UL
<b>Battery qty</b>	1
<b>Battery type or Name</b>	Lithium coin cell (CR1620)
<b>Buzzer</b>	Yes
<b>CE evaluated</b>	Yes
<b>China RoHS compliance</b>	Yes
<b>Communication type</b>	CANBUS MODBUS RS485
<b>Connector kit Code No.</b>	080G0179
<b>Connector kit included</b>	Yes
<b>Contains batteries</b>	Yes
<b>Digital inputs (DI) [pc]</b>	8 pc
<b>Digital outputs (DO) [pc]</b>	6 pc
<b>Display type</b>	Without Display
<b>Division</b>	25
<b>EEE category</b>	5 small equipment (any external dimension &lt; 50 cm)
<b>Enclosure rating IP</b>	IP40
<b>EU RoHS compliance</b>	Yes
<b>EU RoHS exemption clause</b>	No
<b>Frequency [Hz]</b>	50/60 Hz
<b>Function</b>	Programmable Controller
<b>Identical product</b>	080G0169

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

**Product Detail | Program. controller, 6 relays, MCX06D**
**PRODUCT DETAILS**

<b>In scope of WEEE</b>	Yes
<b>Mounting method</b>	DIN rail
<b>Packing format</b>	Single pack
<b>PFAS content [Yes/No]</b>	No
<b>Power consumption [W]</b>	6 W
<b>Product accessories</b>	Electron. control accessories
<b>Quantity per packing format</b>	1 pc
<b>REACH Candidate List substances</b>	Lead (CAS no. 7439-92-1) Lead titanium zirconium oxide (CAS no. 12626-81-2) 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol (CAS no. 119-47-1) 2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol (CAS no. 79-94-7) 1, 2-dimethoxyethane, ethylene glycol dimethyl ether (EGDME) (CAS no. 110-71-4) Triphenyl phosphate (CAS no. 115-86-6)
<b>Real time clock</b>	Yes
<b>SCIP dossier no.</b>	942839ba-75ec-4378-af74-8f61b3b5d9f1
<b>SCIP dossier product name</b>	MCX-06C,06D,06M1V,152V
<b>Serviceable</b>	No
<b>Supply voltage [V] AC</b>	24 V
<b>Supply voltage [V] DC</b>	24 V
<b>Type designation</b>	MCX06D
<b>UL mark</b>	Yes

**For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store** [↗](#)

**Accessories**

**080G0179** [↗](#)

**Electron. control accessories, ACCCNX Connectors MCX/EXC06D, MCX series**

ACCCNX Connectors MCX/EXC06D, Used for product: MCX series, Packing format: Multi pack, Quantity per packing format: 100

**For more information, please use this link to visit the product page on Danfoss Product Store** [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.