

**084Z6170****Temperature sensor, MBT 5252, 250 mm, NPT,1/2-14**

Temperature range [°C]: -50 - 200, Sensor element type: Pt, Sensor elem. resistance [Ohm]: 100, Protection tube material: AISI 316 TI, Electrical connection: Type B, Electrical connection size: Pg 16

PRODUCT DETAILS

Gross weight	0.482 Kilogram
Net weight	0.471 Kilogram
Volume	1.943 Liter
EAN	5702423141906
Type	MBT 5252
Product group	Sensors
Product Name Description	Temperature sensor
Ambient temperature max. [°C]	90 °C
Ambient temperature max. [°F]	194 °F
Approval	CE
CE evaluated	Yes
China RoHS compliance	Out of scope
Connection material	Stainless steel
Connection standard	ANSI/ASME B1.20
Connection type	NPT
Contains batteries	No
EEE category	5 small equipment (any external dimension < 50 cm)
Electrical connection	Type B
Electrical connection size	Pg 16
Enclosure rating IP	IP65
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(c)
Extension length [in]	1.97 in
Extension length [mm]	50 mm
In scope of WEEE	Yes
Insertion length [in]	9.8 in
Insertion length [mm]	250 mm
Insertion type	Fixed
Number of terminals [pcs]	3 pc
Output signal	Ohm
Packing format	Multi pack
Process connection Male/Female	Male
Process connection material	Stainless steel
Process connection size	1/2-14
Process connection standard	ANSI/ASME B1.20.1
Process connection type	NPT
Protection tube diameter [in]	0.394 in

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Temperature sensor, MBT 5252, 250 mm, NPT,1/2-14**PRODUCT DETAILS**

Protection tube diameter [mm]	10 mm
Protection tube material	AISI 316 TI
Quantity per packing format	6 pc
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
SCIP dossier no.	ab5a5d0b-78ac-4b3e-a6f6- bc20d26a29a6
SCIP dossier product name	MBT 3252/5252
Sensor elem. resistance [Ohm]	100 Ohm
Sensor element [pc]	1 pc
Sensor element standard	EN 60751
Sensor element tolerance	Class B
Sensor element type	Pt
Sensor Insert	Exchangeable
Temperature range [°C] [max]	200 °C
Temperature range [°C] [min]	-50 °C
Temperature range [°F] [max]	392 °F
Temperature range [°F] [min]	-58 °F
Type designation	MBT 5252-0011-0250-0700-0000
Wires [pcs]	2 pc

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories

We're sorry, but the requested information is currently unavailable.

This may be because accessories for this product are not available or the data is incomplete.

For the latest and most accurate information, please visit store.danfoss.com.

Thank you for your understanding.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.