

**148F3328** **Safety relief valve, SFA 15, G, 28 bar**

Pressure setting [bar]: 28, Connection type: G, Inlet connection size [in]: 3/4, Outlet connection size [in]: 1, Pressure certificate: TÜV certificate included

**PRODUCT DETAILS**

<b>Gross weight</b>	2.002 Kilogram
<b>Net weight</b>	1.926 Kilogram
<b>Volume</b>	1.354 Liter
<b>EAN</b>	5702428193665
<b>Type</b>	SFA 15
<b>Product group</b>	Safety relief valves
<b>Product Name Description</b>	Safety relief valve
<b>Approval</b>	CE EAC
<b>CE evaluated</b>	Yes
<b>Certified Coef of Disc</b>	0.73 kg
<b>China RoHS compliance</b>	Out of scope
<b>Comments</b>	0
<b>Connection Internal/External</b>	External
<b>Connection size [in]</b>	1/2 in
<b>Connection size [mm]</b>	15 mm
<b>Connection standard</b>	ISO 228-1
<b>Connection type</b>	G
<b>Contains batteries</b>	No
<b>Direction</b>	Angleway
<b>EU RoHS compliance</b>	Out of scope
<b>Flow area [in2]</b>	0.206 in <sup>2</sup>
<b>Flow area [mm2]</b>	133 mm <sup>2</sup>
<b>Flow diameter [in]</b>	0.512 in
<b>Flow diameter [mm]</b>	13 mm
<b>Fluid Group</b>	1
<b>Inlet connection size [in]</b>	3/4
<b>Lift [mm]</b>	4.8 mm
<b>Nominal diameter</b>	DN < 15
<b>Outlet connection size [in]</b>	1
<b>Packing format</b>	Single pack
<b>PED category</b>	IV
<b>Pressure certificate</b>	TÜV certificate included
<b>Pressure setting [bar]</b>	28 bar
<b>Pressure setting [psig]</b>	406 psig
<b>Product description</b>	Safety Relief Valve
<b>Quantity per packing format</b>	1 pc
<b>REACH Candidate List substances</b>	Lead (CAS no. 7439-92-1)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## PRODUCT DETAILS

### Refrigerants

R134a, R170, R22, R401A, R402A, R404A, R407A, R407B, R407C, R407F, R409A, R410A, R421A, R502, R600, R600a, R717, R744, R507A, R1234yf, R1234ze(E), R125, R152a, R227ea, R236fa, R245fa, R290, R32, R407H, R413A, R417A, R422A, R422B, R422D, R438A, R442A, R444B, R447A, R447B, R448A, R449A, R449B, R450A, R452A, R452B, R452C, R454A, R454B, R454C, R455A, R463A, R512A, R513A, R513B, R515A, R515B, R516A

SCIP dossier no.	b6d989c8-42d2-47d3-85cd-8518f10699b1
SCIP dossier product name	SFA 15
Temperature range [°C] [max]	100 °C
Temperature range [°C] [min]	-50 °C
Temperature range [°F] [max]	212 °F
Temperature range [°F] [min]	-58 °F

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

## Accessories

Image  
coming  
soon

### 148F3079 [🔗](#)

#### Spare part, SFA 15, Nipple and gasket set

Product Type: Spare part, Used for product: SFA 15, Type designation: Nipple and gasket set



### 148F3029 [🔗](#)

#### Spare part, DSV 1, Gaskets

Product Type: Spare part, Used for product: DSV 1, Type designation: Gaskets

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.