



 PRODUCT-DETAILS

SSPLHC16/25M

16MM SS-TPR COAT CONDUIT 25M - BL



General Information

Extended Product Type	SSPLHC16/25M
Product ID	7TCA296030R0415
EAN	5020963800900
Catalog Description	16MM SS-TPR COAT CONDUIT 25M - BL
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 16mm, Outside Diameter 17.8mm, Inside Diameter 12.5mm, Static Bend Radius 50mm, Reel Length 25 Meters, Thermoplastic Rubber Cover with Stainless Steel Core, Black

Additional Information

Product Main Type	ADAPTAFLEX FLEXIBLE CABLE PROTECTION
Application	Liquid Tight - Extreme Temperature Environments
Product Type	Extreme Temperature Flexible Conduit

Ordering

EAN	5020963800900
-----	---------------

UPC

786210289786

Dimensions

Product Net Depth / Length	25 m
Outside Diameter	17.8 mm

Technical

Number of Batteries	0
Color	Black
Material	Stainless Steel Core with Thermoplastic Rubber Cover

Environmental

WEEE Category	Product Not in WEEE Scope
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Container Information

Package Level 1 Units	1 piece
Package Level 1 EAN	5020963800900
Package Level 1 Height	6 in 152 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 1 Width	16 in 406 mm

Certificates and Declarations

Data Sheet, Technical Information	7TKK001231
Declaration of Conformity - CE	9AKK107492A9618
RoHS Declaration	9AKK107992A8994
REACH Declaration	9AKK107992A8994

External Classifications and Standards

ETIM 8	EC001179 - Protective metallic hose
ETIM 9	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

