



 PRODUCT-DETAILS

SSPLHC32/25M

32MM SS-TPR COAT CONDUIT 25M - BL



General Information

Extended Product Type	SSPLHC32/25M
Product ID	7TCA296030R0418
EAN	5020963800931
Catalog Description	32MM SS-TPR COAT CONDUIT 25M - BL
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 32mm, 1 Inch US Conduit Size, Outside Diameter 33.1mm, Inside Diameter 26.7mm, Static Bend Radius 145mm, Reel Length 25 Meters, Thermoplastic Rubber Cover with Stainless Steel Core, Black

Additional Information

Product Main Type	ADAPTAFLEX FLEXIBLE CABLE PROTECTION
Application	Liquid Tight - Extreme Temperature Environments
Product Type	Extreme Temperature Flexible Conduit

Ordering

EAN	5020963800931
-----	---------------

UPC 786210289816

Dimensions

Product Net Depth / Length	25 m
Outside Diameter	33.1 mm

Technical

Number of Batteries	0
Color	Black
Material	Stainless Steel Core with Thermoplastic Rubber Cover

Environmental

WEEE Category	Product Not in WEEE Scope
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Container Information

Package Level 1 Units	1 piece
Package Level 1 EAN	5020963800931
Package Level 1 Height	10.62 in 270 mm
Package Level 1 Depth / Length	26.77 in 680 mm
Package Level 1 Width	26.77 in 680 mm

Certificates and Declarations

Data Sheet, Technical Information	7TKK001231
Declaration of Conformity - CE	9AKK107492A9618
RoHS Declaration	9AKK107992A8994
REACH Declaration	9AKK107992A8994

External Classifications and Standards

ETIM 8	EC001179 - Protective metallic hose
ETIM 9	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

