

SIMATIC IPC PX-39A 19" multi-touch (1920 x 1080); neutral front; Intel(R) UHD graphics onboard; 4 x USB 3.2; Ethernet (10/100/1000); PCIe (optional); Intel Xeon W-11155MLE (1.8/3.1 GHz, 4C/8T); 8 GB and NVRAM (M.2 module); M.2 SSD 480 GB without 2nd mass storage; Windows 11 IoT Enterprise 2024 LTSC for Celeron, Xeon W-11155MLE, Xeon W-11555MLE; without option 1; restore stick image with D&D and software image (if selected) only via OSD (online portal) 110/230 V AC industrial power supply unit with NAMUR; without power supply cord;

Display	
Design of display	19" TFT multi-touch
Screen diagonal	18.5 in
Resolution (pixels)	
• Horizontal image resolution	1 920 pixel
• Vertical image resolution	1 080 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Input device	
• Mouse, at front	No
Keyboard fonts	
• Function keys	No
• alphanumeric keyboard	No
Touch operation	
• Design as multi-touch screen	Yes; Projective-capacitive
Installation type/mounting	
central design	Yes
distributed design	No
Mounting in portrait format possible	Yes
Power loss	
In full configuration	24 V DC: max. 82 W, 110 ... 230 V AC
Dimensions	
Width of the housing front	464 mm
Height of housing front	294 mm
Mounting cutout, width	448 mm
Mounting cutout, height	278 mm
mounting depth	91.6 mm
mounting depth with PCI expansion	117 mm
Weights	
Weight, approx.	8 kg
Approvals / Certificates	
General Product Approval	



[Miscellaneous](#)



[BIS CRS](#)

General Product Approval

Dangerous goods

[KC](#)

[Dangerous goods information](#)

last modified:

12/18/2025 