

Data sheet for SIMOTICS S-1FT7

Article No. : **1FT7064-5WK71-1CG1-Z
X09**




Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

Rated speed	6,000 rpm
Number of poles	10
Rated torque (100 K)	14.2 Nm
Rated current	20.00 A
Static torque (60 K)	12.8 Nm
Static torque (100 K)	16.0 Nm
Stall current (60 K)	16.30 A
Stall current (100 K)	20.20 A
Rotor moment of inertia	12.90 kgcm ²
Efficiency	92.0 %

Physical constants

Torque constant	0.79 Nm/A
Voltage constant at 20° C	49.6 V/1000*min ⁻¹
Winding resistance at 20° C	0.18 Ω
Rotary field inductance	1.8 mH
Electrical time constant	10.00 ms
Mechanical time constant	1.10 ms
Thermal time constant	2 min
Shaft torsional stiffness	35,000 Nm/rad
Net weight of the motor	13.7 kg

Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	63
Cooling	Water cooling
Radial runout tolerance	0.040 mm
Concentricity tolerance	0.100 mm
Axial runout tolerance	0.100 mm
Vibration severity grade	Grade A
Degree of protection	IP65
Design acc. to Code I	IM B5 (compatible with 1FT6)
Temperature monitoring	Pt1000 temperature sensor
Color of the housing	Anthracite RAL 7016
Shaft end type	Plain shaft
Sensor design	Encoder AM24DQI: Absolute encoder 24 bit (resolution 16777216, encoder-internal 2048 S/R) + 12 bit Multiturn (traversing range 4096 revolutions) - with signal connection RJ45
Electrical connection	Connector turnable
Connector size	1

Optimum operating point

Optimum speed	6,000 rpm
Optimum power	8.9 kW

Limiting data

Max. permissible speed (mech.)	9,000 rpm
Max. permissible speed (inverter)	8,000 rpm
Maximum torque	40.0 Nm
Maximum current	67.00 A

Recommended Motor Module

Rated inverter current	30.00 A
Maximum inverter current	90.00 A
Maximum torque	40.0 Nm

Special design

X09 Paint finish anthracite, similar to RAL 7016