



V330-F102M03M-NNX

V330 Code Reader, 0.3 MP monochrome, Medium view, Fixed focus 102 mm, No outer light, X-Mode decoder, Ethernet TCP/IP, PROFINET, PoE, IP40

Specifications

Number of pixels	0.3 MP
Camera type	Monochrome
Autofocus	✘
Focus distance	102-102 mm
Field of view (width)	67-67 mm
Decoder type	X-Mode (advanced 1D+2D+DPM)
Frame rate	60 fps
Illumination	Inner LEDs only
Communication port(s)	Ethernet TCP/IP, PROFINET Slave, PoE
Image width	752 pixels
Image height	480 pixels
Shutter type	Global
Product Height (unpacked)	24.1 mm
Product Width (unpacked)	40 mm
Product Depth (unpacked)	63 mm
Product Weight (unpacked)	72 g
Degree of protection (IP)	IP40


V330-AF1

V/F 3x0-F Diffuser Kit, Peel and Stick Accessory, Exterior to unit

V330-AF2

V/F 3x0-F Polarizer Kit, Peel and Stick Accessory, Exterior to unit

CAD Library



Code Reader Technical Manual

EN PDF 1.08 MB



Code Reader Group Catalog

EN PDF 5.63 MB



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



Firmware v2.2.0 Software

EN ZIP 35.9 MB



MicroHAWK Optics and Lighting Accessory Kit Installation Manual

EN PDF 8.25 MB



MicroHAWK V Series Brochure

EN PDF 1.58 MB



MicroHAWK V Series Users Manual

EN PDF 47.9 MB



MicroHAWK V Series Communications Manual

EN PDF 6.7 MB



MicroHAWK V330-F Datasheet

EN PDF 1.49 MB




NX-series -[Ethernet TCP/IP]- V330-F, V430-F Code Readers Connection Guide

EN PDF 2.89 MB



OMRON_Microscan_DDU_Installation Software

EN ZIP 40.3 MB



V430-F, V330-F EtherNet/IP EDS file

EN ZIP 389 KB



Omron V430-F, V330-F PROFINET GSDML file

EN ZIP 353 KB



Traceability Solutions Toolbox Software

EN ZIP 6.05 MB