



V275-P46Z61060-CC

V275 print quality inspection system, integrated into a 600 dpi resolution Zebra ZT610 printer, print and verify labels up to 104 mm wide at speeds up to 152 mm per second.

Specifications

In-line print quality inspection system	✓
Sensor	600 dpi line scan camera
Printer operation	Continuous, Tear-off
Printer model	ZT610
Printer resolution	600 dpi
Decoder type	1D, 2D
Functions	Blemish detection, OCR, OCV
Max. inspection speed	152 mm/s
Max. inspection width	104 mm
Max. web width	114 mm
Min. inspection width	25 mm
Max. label length	305 mm
Min. label length	20 mm
Max. media thickness	0.28 mm
Min. media thickness	0.05 mm

Accessories

V275-ACEAN028-01	V275 calibration conformance test card, 4", serialized, undated
V275-ALCBL0ZT	V275 light tower cable, unterminated, for ZEBRA ZT
V275-ALRYGZZT	Light tower for use with the V275. Includes light tower and cable for connecting with Zebra printer.
V275-APIQQ03-01	V275 IQ/OQ/PQ procedure, 300 DPI printers

Spare parts

V275-RPCC0ZEB	Replacement printer control cable, V275
V275-RRH04ZEB	Kit, V275, 4" read head replacement for ZEBRA ZT



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



LVS/V Series Barcode Verification System

Flyer

EN PDF 2.7 MB



V275 Brochure

EN PDF 858 KB



V275 Operation Manual

EN PDF 18.9 MB



V275 IQ/OQ/PQ Guidelines

Leaflet

EN PDF 1020 KB



V275 Product Guide Leaflet

EN PDF 297 KB



V275 Series Datasheet

EN PDF 285 KB



V275 Software Software

EN ZIP 314 MB



V275 Success Story Leaflet

EN PDF 2.07 MB