



V450-HDS3608-0001

Code reader, handheld, DPM (Direct part mark), Wired

Specifications

Decoder type	X-Mode (advanced 1D+2D+DPM)
Range	0-147 mm
2D Code symbologies supported	Aztec, DotCode, GS1 Data Matrix (ECC200), Han Xin, Micro QR, MicroPDF417, PDF417, Postal Codes, QR Code, TLC-39
Bar Code symbologies supported	Codabar, Code 11, Code 128, Code 39, Code 93, GS1 Databar, Interleaved 2 of 5, Korean 3 of 5, MSI Plessey, UPC/EAN
Degree of protection (IP)	IP65/IP67
Communication port(s)	Serial RS-232C, USB
Supply voltage DC	4.5-5.5 V
Code marking type	Direct part marking
Housing type	Ruggedised
Connection type	Wired

Fits to



12-9000943-01

Cable, USB, Shielded, 4.6 m, Ext. 12 V, HDS-3600/V450-H *** Power Supply Required ***



12-9000947-01

Cable, USB, Shielded, 4.6 m, HDS-3600/V450-H

Accessories



12-9000942-01

Cable, USB, Shielded, 2 m, Ext. 12 V, HDS-3600 / V450-H *** Power Supply Required ***



12-9000943-01

Cable, USB, Shielded, 4.6 m, Ext. 12 V, HDS-3600/V450-H *** Power Supply Required ***



12-9000946-01

Cable, USB, Shielded, 2 m, HDS-3600/V450-H



12-9000947-01

Cable, USB, Shielded, 4.6 m, HDS-3600/V450-H



12-9000953-01

Cable, RS-232, DB9 female, 2 m, straight, HDS-3600 / V450-H

12-9000960-01

AC Power cord, 2.5 m, EU, C13 connector




98-9000181-01

Kit, Power supply for cradle / charger, HDS-3678/V450-H, AC Power Cord Required

98-9000186-01

Stand, Intelligent, HS-360X, V450-H

CAD Library



Code Reader Technical Manual

EN PDF 1.08 MB



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



OMRON_Microscan_DDU_Installer_4.0.0. Software

EN ZIP 40.3 MB



Traceability Solutions Toolbox Software

EN ZIP 6.05 MB



V410-H and V450-H Handheld Barcode Reader Users Manual

EN PDF 21.2 MB



V450-H Handheld Reader Datasheet

EN PDF 2.14 MB



V450-H Quick Start Guide Wired Practice Guide

EN PDF 5.65 MB



V450-H Quick Start Guide Wireless Practice Guide

EN PDF 5.4 MB



WebLinkPC 3.0.0.3004 Software

EN ZIP 168 MB