



## F430-F000L12M-HRA

F430 Smart Camera, 1.2 MP monochrome, Long range, Autofocus 75-1200 mm, High brightness red light, AutoVISION, Ethernet TCP/IP, EtherNet/IP, PROFINET, IP65/IP67

# Specifications

Camera family	F430
Number of pixels	1.2 MP
Camera type	Monochrome
Autofocus	✓
Focus distance	78-1200 mm
Focal length	16 mm
Field of view (width)	24-436 mm
Frame rate	40 fps
Shutter type	Global
Illumination	High brightness red LED ring
Software option(s)	AutoVISION
Image sensor type	CMOS
Image width	1280 pixels
Image height	960 pixels
Communication port(s)	EtherNet/IP, Ethernet TCP/IP, PROFINET Slave, Serial RS-232C
Degree of protection (IP)	IP65/IP67
Application	Code reading, Code verification, Counting, Measurement inspection, OCR / OCV, Presence / Absence

## CAD Library



**AutoVISION Industrial Protocol Manual Users Manual**

EN PDF 9.68 MB



**AutoVISION Software - Quick Start Guide Users Manual**

EN PDF 14.5 MB



**AutoVISION WebMonitor Users Manual**

EN PDF 5.95 MB



**AutoVISION\_530\_3025\_016 Software**

EN ZIP 979 MB



**Communications Connection Guide Integration guide**

EN PDF 4.62 MB



**EAC Mark removal Discontinuation Notice**

EN PDF 221 KB



**EtherNet/IPTM Connection Guide Integration guide**

EN PDF 4.6 MB



**MicroHAWK F Series 0F Users Manual**

EN PDF 18.4 MB



**MicroHAWK F430-F Datasheet**

EN PDF 6.71 MB



**MicroHAWK F430-F/F420-F Series Brochure**

EN PDF 4.17 MB




**MicroHAWK F440-F/F430-F/F420-F Series - Smart Camera Users Manual**

EN PDF 9.09 MB



**MicroHAWK Optics and Lighting Accessory Kit Installation Manual**

EN PDF 8.25 MB



**OMRON\_Microscan\_DDU\_Ins Software**

EN ZIP 40.3 MB




**Selection Guide for Vision Sensors Brochure**

EN PDF 991 KB



**TCP/IP Connection Guide Integration guide**

EN PDF 4.14 MB



**Traceability Solutions Toolbox Software**

EN ZIP 6.05 MB

