



## F430-F000N12M-HRA

F430 Smart Camera, 1.2 MP monochrome, Narrow view, Autofocus 40-150 mm, High brightness red light, AutoVISION, Ethernet TCP/IP, EtherNet/IP, PROFINET, IP65/IP67

# Specifications

Camera family	F430
Number of pixels	1.2 MP
Camera type	Monochrome
Autofocus	✓
Focus distance	40-150 mm
Focal length	16 mm
Field of view (width)	16-45 mm
Frame rate	40 fps
Shutter type	Global
Illumination	High brightness red LED
Software option(s)	AutoVISION
Image sensor type	CMOS
Image width	1280 pixels
Image height	960 pixels
Communication port(s)	EtherNet/IP, Ethernet TCP/IP, PROFINET Slave, Serial RS-232C
Degree of protection (IP)	IP65/IP67
Application	Code reading, Code verification, Counting, Measurement inspection, OCR / OCV, Presence / Absence

## CAD Library



**AutoVISION Industrial Protocol Manual Users Manual**

EN PDF 9.68 MB




**AutoVISION Software - Quick Start Guide Users Manual**

EN PDF 14.5 MB



**AutoVISION WebMonitor Users Manual**

EN PDF 5.95 MB



**AutoVISION\_530\_3025\_016 Software**

EN ZIP 979 MB



**Communications Connection Guide Integration guide**

EN PDF 4.62 MB



**EAC Mark removal Discontinuation Notice**

EN PDF 221 KB



**EtherNet/IPTM Connection Guide Integration guide**

EN PDF 4.6 MB



**MicroHAWK F Series 0F Users Manual**

EN PDF 18.4 MB



**MicroHAWK F430-F Datasheet**

EN PDF 6.71 MB



**MicroHAWK F430-F/F420-F Series Brochure**

EN PDF 4.17 MB




**MicroHAWK F440-F/F430-F/F420-F Series - Smart Camera Users Manual**

EN PDF 9.09 MB



**MicroHAWK Optics and Lighting Accessory Kit Installation Manual**

EN PDF 8.25 MB



**OMRON\_Microscan\_DDU\_Ins Software**

EN ZIP 40.3 MB




**Selection Guide for Vision Sensors Brochure**

EN PDF 991 KB



**TCP/IP Connection Guide Integration guide**

EN PDF 4.14 MB



**Traceability Solutions Toolbox Software**

EN ZIP 6.05 MB

