



E3ZM-B86

Photoelectric sensor, rectangular housing, stainless steel, red LED, retro-reflective, transparent object, 500 mm, with teach-button, PNP, Light-ON/Dark-ON, M8 4-pin connector

Specifications

Shape	Cuboid
Sensing method	Retro-reflective
Sensing distance	500 mm
Sensing distance (min.)	100 mm
Setting method	Teach-In
Connection method	Connector M8 - 4 pin
Output type	PNP
Operation mode	Dark-ON, Light-ON
Response time	1 ms
Material housing	Stainless steel
Thread size	Other
Product Width (unpacked)	10.8 mm
Product Height (unpacked)	31 mm
Product Depth (unpacked)	21 mm
Type of light	Polarized red light
Power supply voltage	10-30 V
Features	M.S.R., Transparent detection (PET bottle and tray)
Degree of protection (IP)	IP67/IP69K

Accessories



E39-L150

Sensor mounting Bracket for E3Z, 100mm high post



E39-L151

Sensor mounting Bracket, for E3Z, 200mm high post



E39-L203

Rear mounting bracket for E3AS-F/L models



E39-L211

L-shaped mounting bracket for E3AS-F/L models



E39-L212

Horizontal protective cover bracket for E3AS-F/L cable and pigtail models



E39-L214

Protective metal cover for E3AS, horizontal surface mounting



E39-L44

Mounting bracket for E3Z sensor, rear mounting



E39-RP1

Reflector, polarizing, to use with E3ZM-B, 44mm x 64mm

Related products



M8 Connectors & Cordsets

Industrial connectors & cordsets for any application

Downloads

CAD Library



E3Z Brochure

EN PDF 1.34 MB



E3ZM-B Series Datasheet

EN PDF 2.87 MB



EAC Mark removal Discontinuation Notice

EN PDF 221 KB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 25 December, 2025. Click here for [terms of use](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU