



NX-TS2201

2 Temperature Sensor Inputs, Pt100 (3-wire), Pt1000, resolution 0.1 °C, 250 ms/Unit, screwless push-in connector, 12 mm wide

Specifications

I/O system	NX I/O Bus
Type of module	Analog I/O
Number of analog inputs	2
Temperature input type	Pt100, Pt1000
Linear analog input type	None
Resolution of the analog inputs	14 Bit
Input circuit type	Single-ended
Number of analog outputs	0
Linear analog output type	None
Resolution of the analog outputs	0 Bit
Conversion time	250 ms/unit
Signal processing	Free running
IO-Link master	✘
I/O connection type	Push-in
Number of I/O connectors	1
Detachable I/O connector	✔
Suitable for safety functions	✘
SIL according to IEC 61508	None
Degree of protection (IP)	IP20
Product Height (unpacked)	100 mm
Product Width (unpacked)	12 mm
Product Depth (unpacked)	80 mm
Product Weight (unpacked)	70 g

Accessories



NX-AUX02

Terminal block coding pins for 10x NX I/O units (terminal block: 30 pins, unit: 30 pins)



NX-HB3201

Heater Burnout Detection Unit, 4 CT inputs, 4 PNP Outputs, screwless push-in connector, 12 mm wide

Spare parts



NX-TBA162

Replacement screwless push-in connector with 16 wiring terminals (marked A+B)

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



IO-Link Series Brochure

EN PDF 6.41 MB



Machine Safety Solution Brochure

EN PDF 2.86 MB



NX-HAD Brochure

EN PDF 1.22 MB



NX-HTC/NX-TC/EJ1/E5DC-B Temperature control units Flyer

EN PDF 3.28 MB



NX-series Reference Manual

EN PDF 1.45 MB



NX-series I/O system Brochure

EN PDF 8.37 MB



NX-series Temperature Input Unit / Heater Burnout Detection Unit - NX-TS/HB Datasheet

EN PDF 4.88 MB



NX-series Temperature Input and Heater Burnout Detection Units Users Manual

EN PDF 9.89 MB



Omron NX-ECC20x EtherCAT ESI file

EN ZIP 1.51 MB



Sysmac Catalogue

EN PDF 43.5 MB



Sysmac: A Fully Integrated Platform Brochure

EN PDF 19.1 MB